

DRIVER: _____	TRACK: _____	TRANSMITTER: _____	BATTERY: _____	TIRES: _____
DATE: _____	SURFACE: ASPHALT ☐ CARPET ☐	RECEIVER: _____	MOTOR: _____	ADDITIVE: _____
OUTSIDE TEMPERATURE°C: _____	LAYOUT: TECHNICAL ☐ MIXED ☐ FAST ☐	SERVO: _____	PINION: _____	WARMER C°: _____
TRACK TEMPERATURE°C: _____	TRACTION: LOW ☐ MEDIUM ☐ HIGH ☐	STEERING EXPO: _____	SPUR: _____	WARMER TIME: _____
VER. 3101-1	RACE: _____ RESULT: _____	STEERING SPEED: _____		SIDEWALL GLUE: _____

☐ CLIP ☐ O-RING ☐ ACTIVE ☐ FIXED FF (mm) _____ FR (mm) _____ RIDE HEIGHT (mm) _____ UPTAVEL LIMIT (mm) _____ INSIDE ☐ OUTSIDE ☐ CAMBER° _____ TOE OUT° _____ DOWNSTOP(mm) _____ CASTER° _____ OUT (3mm) ☐ 2,5mm ☐ 2,0mm ☐ 1,5mm ☐ 1,0mm ☐ 0,5mm ☐ IN (0mm) ☐	 F/R ☐ VERTICAL ☐ VERTICAL ☐ [ONLY USE WITH INNER POSITION ON THE LOWER WISHBONE] HORIZONTAL ☐ HORIZONTAL ☐ BYPASS ☐ BYPASS ☐ PISTON OPT. ☐ PISTON OPT. ☐ SPRING _____ SPRING _____ OIL# _____ OIL# _____ 1.1 1.2 1.3 1.1 1.2 1.3 -0,5 0 0,5 -0,5 0 0,5	CAMBER° (mm) _____ TOE IN° _____ DOWNSTOP(mm) _____ INSIDE ☐ OUTSIDE ☐ RIDE HEIGHT (mm) _____ UPTAVEL LIMIT (mm) _____ UPPERARM POSITION _____ OUT (3mm) ☐ 2,5mm ☐ 2,0mm ☐ 1,5mm ☐ 1,0mm ☐ 0,5mm ☐ IN (0mm) ☐
---	---	--

☐ CUT ☐ CUT TYPE (mm) _____ ROD POS. _____ STD ☐ OPT ☐ STEERING° _____ OUTSIDE _____ INSIDE _____ INFO _____ _____ _____	 CHASSIS TYPE _____ CAR WEIGHT (g) _____ MOTORMOUNT SCREW _____ WEIGHT UNDER BATTERY (g) _____ 1 2 3 4 g (UNDER PINION) g (UNDER ESC) g (UNDER RECEIVER) WEIGHT (g) F _____ R _____ 50% / 50% = CENTER (± 0.5% each step) WEIGHT ON A2440 (g) _____ WIDE ☐ NARROW ☐ _____ (mm) _____	 TYPE (mm) _____ OIL# _____ OIL (g) _____ (A2248D alu) ☐ SHIM (mm) _____ BODYSHELL & WING TYPE _____ SIDE STIFFENER ☐ _____ (mm) _____ DISTANCE TO CHASSIS _____ _____ (mm) _____
---	---	---