

DRIVER: _____	TRACK: _____	TRANSMITTER: _____	BATTERY: _____	TIRES: _____
DATE: _____	SURFACE: ASPHALT ☐ CARPET ☐	RECEIVER: _____	MOTOR: _____	ADDITIVE: _____
OUTSIDE TEMPERATURE°C: _____	LAYOUT: TECHNICAL ☐ MIXED ☐ FAST ☐	SERVO: _____	PINION TYPE & T: _____	WARMER C°: _____
TRACK TEMPERATURE°C: _____	TRACTION: LOW ☐ MEDIUM ☐ HIGH ☐	STEERING EXPO: _____	SPUR TYPE & T: _____	WARMER TIME: _____
VER. 3101-1	RACE: _____ RESULT: _____	STEERING SPEED: _____		SIDEWALL GLUE: _____

☐ CLIP ☐ O-RING ☐ ACTIVE ☐ FIXED FF (mm) _____ FR (mm) _____ CAMBER° _____ TOE OUT° _____ DOWNSTOP(mm) _____ RIDE HEIGHT (mm) _____ INSIDE ☐ OUTSIDE ☐ UPTRAVEL LIMIT (mm) _____ CASTER° _____ OUT (3mm) ☐ 2,5mm ☐ 2,0mm ☐ 1,5mm ☐ 1,0mm ☐ 0,5mm ☐ IN (0mm) ☐	☐ F/R ☐ _____ [mm] _____ VERTICAL ☐ VERTICAL ☐ (ONLY USE WITH INNER POSITION ON THE LOWER WISHBONE) HORIZONTAL ☐ HORIZONTAL ☐ BYPASS ☐ BYPASS ☐ PISTON OPT. ☐ PISTON OPT. ☐ SPRING _____ SPRING _____ OIL# _____ OIL# _____ [mm] _____ [mm] _____ 1.1 1.2 1.3 1.1 1.2 1.3 -0.5 0 0.5 -0.5 0 0.5	CAMBER° [mm] _____ TOE IN° _____ DOWNSTOP(mm) _____ INSIDE ☐ OUTSIDE ☐ RIDE HEIGHT (mm) _____ UPTRAVEL LIMIT (mm) _____ CASTER° _____ OUT (3mm) ☐ 2,5mm ☐ 2,0mm ☐ 1,5mm ☐ 1,0mm ☐ 0,5mm ☐ IN (0mm) ☐
--	--	---

☐ CUT ☐ CUT TYPE (mm) _____ ROD POS. ☐ STD ☐ OPT ☐ STEERING° _____ OUTSIDE _____ INSIDE _____ INFO	☐ UP (KIT) ☐ LOW (MSE#MA2051) CHASSIS TYPE _____ CAR WEIGHT (g) _____ WEIGHT BALANCE F%/R% _____ MOTORMOUNT SCREW _____ WEIGHT UNDER BATTERY (g) _____ 1 2 3 4 g (UNDER PINION) g (UNDER ESC) g (UNDER RECEIVER) 50% / 50% = CENTER (± 0.5% each step) WEIGHT (g) F _____ R _____ WEIGHT ON A2440 (g) _____ WIDE ☐ NARROW ☐ [mm] _____	☐ UP (KIT) ☐ LOW (MSE#MA2051) TYPE (mm) _____ OIL# _____ OIL (g) _____ (A2248D alu) ☐ SHIM (mm) _____ BODYSHELL & WING TYPE _____ SIDE STIFFENER ☐ DISTANCE TO CHASSIS _____ WINGLET ☐
---	--	--