



Setup Sheet

v1.0 by Awesome Bob

NORSEMEN

Race:

Driver:

Date:

Track:
Notes:

Surface

- ☐ CRC Black
☐ CRC Grey
☐ ETS
☐ Asphalt
☐ Other

Layout

- ☐ Open
☐ Mixed
☐ Technical

Traction

- ☐ High
☐ Med-High
☐ Med
☐ Med-Low
☐ Low

Condition

- ☐ Smooth
☐ Mixed
☐ Bumpy

Temperature

Surface:

- ☐ C
☐ F

Air:

- ☐ C
☐ F

Humidity

- ☐ High
☐ Medium
☐ Low

Qual:

Race:

Best lap:

Spur:

Pinion:

FDR:

Toe Angle °

Tires: Glue Diam: mm min Warmers: ° min

RC Shim mm

Caster mm

Wing Shim ☐ 0.5mm ☐ 1.0mm

Front Ride Height mm

Droop mm

Side Springs

Spring Preload

Mid Ride Height mm

Droop mm

Rear Ride Height mm

Axle Shim mm

Top Deck ☐ Long ☐ Short

Wheel Base Insert mm ☐ Forward ☐ Reward

Tires: Glue Diam: mm min Warmers: ° min

Side Link Position ☐ Long ☐ Short ☐ Straight ☐ Angled

Link Shim mm

Link Shim mm

Tube Oil CST

Shock ☐ Long ☐ Short

Shock Mount Shims mm

Height Shim mm

Axle ☐ Steel ☐ Graphite ☐ Other

Shim under Bellcrank mm

Bellcrank ☐ Long ☐ Short ☐ Topdeck screw

Bump Steer mm

Ackerman

Additive: Surface: Time: min

Additive: Surface: Time: min

Caster Angle ° Reactive Caster ☐ 0° ☐ 5° ☐ 10° Shim mm Shim mm Shim mm Springs	King Pin Lube CST A-arm Height mm ☐ Long ☐ Short ☐ Wide ☐ Narrow	Plate ☐ Above ☐ Below Bump Steer mm Ball ☐ Above ☐ Below Knuckle ☐ Inline ☐ Trailing	Steering Angles Inside ° Outside ° Servo Saver Weight Balance g % / % Aerodynamics Body: F. Wing: R. Wing:	Shock Spring: CST Oil: % Piston: % Rebound: % Electronics Motor: Timing: ESC: Battery: Servo: Rx: Notes:	V-Link Setting ☐ B3 ☐ B4 ☐ A1 ☐ A2 ☐ A3 ☐ A4 Differential ☐ Ball ☐ Gear ☐ Spool ☐ Loose ☐ Tight CST Rear Wing Position #
---	--	--	--	--	---