

SP2 SETUP SHEET

RCMAKER

DRIVER	Alex Everett	DATE	11 / 10 / 26	BEST LAP		LAYOUT	☐ TECHNICAL ☐ MIXED ☐ FLOWING
TRACK	EWS	CLASS	17.5T	BEST RUN		TEMP	☐ TRACK ☐ AIR
EVENT	EWS 17.5 Stock - Rnd 1	RESULT		SURFACE	Carpet	TRACTION	☐ LOW ☐ MEDIUM ☐ HIGH

TRANSMISSION

FRONT	REAR	
DRIVE ☐ SPOOL ☐ DIFF	DIFF OIL 8K cst	
OIL ☐ ONLY IF USING DIFF	DIFF OIL WEIGHT 1.5 g	
PITCH ☐ 64 ☐ 48	BELTS ☐ LF ☐ STD ☐ HD	
SPUR 100	PIN 45	FDR 4.22

SHOCKS

FRONT	REAR
4.5 coils	4.25 coils
450	CST ☐ OIL WT ☐ 550
☐ STD	☐ STD
☐ PSS ☐ PRG	☐ PSS ☐ PRG
6.7 mm	LENGTH 6.7 mm

TIRES

TIRES	Rush 30
ADDITIVE	V5
ADDITIVE TIME	Fr 10 min/Rr 10 min
WARMER TIME	Fr min/Rr min
WARMER TEMP	Fr deg/Rr deg

BODY

TYPE	Twister Speciale
WEIGHT	71 grams
WING	MR33 Twister
POSITION	LOWER WINDSCREEN MOLD LINE TO CENTRE FRONT BODY POST
HEIGHT	8 mm

ELECTRONICS

RADIO	ST E280
SERVO	GTS-2
ESC	Elceram Nitride
MOTOR	Zombie
BATTERY	Zombie 6200

NOTES

Consider raising lower arms .5mm to reduce chassis roll a touch.

Raise inner upper links to free the car up more

Be braver!!!!

FRONT

CAMBER	1.5	deg
CASTER	5	deg
TOE OUT	1	deg
RIDE HEIGHT	5.2	mm
DROOP	ARM AXLE	23.6 mm
DIFF HEIGHT	LOW HIGH	
ANTI ROLL BAR	1.0 1.1 1.2 1.3	
STEERING LOCK	INSIDE OUTSIDE	

REAR

CAMBER	2	deg
CASTER	-2.5	deg
TOE IN	3	deg
RIDE HEIGHT	5.4	mm
DROOP	ARM AXLE	22.6 mm
DIFF HEIGHT	LOW HIGH	
ANTI ROLL BAR	1.0 1.1 1.2 1.3	

FRONT	REAR
50 %	50 %
WEIGHT BIAS	
1.5 mm	TOE GAIN

TOPDECK

FRONT	TYPE ☐ 1 PC ☐ 2 PC	REAR
THICKNESS		
MATERIAL	C/F FRP	C/F FRP
BRACE	CUT FLEX SOLID	

CHASSIS

FRONT	MOTORMOUNT	REAR
STIFFENER	CHASSIS TYPE	STIFFENER
BRASS CARBON	2.2MM CARBON	CARBON
	1.5MM ALUMINIUM	BRASS
	1.2MM SPRING STEEL	TENSIONER
	OTHER	