REFLEXIACING FX28									
DATE		/ /	TRACK			TRACTION	HIGH I	LOW	
DRIVER N	NAME E	ASIC SETUP	COUNTRY			TEMP.	AIR	TRACK	
EVENT			BEST LAP TI	ME	QUALIFYIN	NG POSITION	FINAL	POSITION	
	DIFFERENTIAL GEAR DIFF GREASE BALL DIFF INTIGHT LOOSE RIDE HEIGHT 2.0 Damper Disc C	/CST /mm Roll Damper Oil		DAMPER DISC OIL REFLEX GREEN DROOP 0.5 DITCH GIMBAL OIL	/CST //CST //MM //CST	KV 050	REFLEX CO REFLEX CO FRONT SPI SOFT HARD OTHERS TOE ANGLE 1 O RIDE HEIGH 2.	SHIMS D.25 /mm L RANGE /CST RING MEDIUM EX. HARD UT DEG 5 /mm HT O /mm	
FRO	E SETTING DNT	REAR TIRE MARKA 10	PINON GEAR 12	SPUI 2 T GEAR		BODY 5	RADBODY		
TIRE	EFLEX 40			MC-1	RECEIVER		SERVO	REFLEX	
	REFLEX	WHEEL	BATTERV	LEX 400MAH	CHARGE CURRENT	1.0	TOTAL A WEIGHT	160 /grams	
OFF	O /mm METER 22.5 /mm	OFFSET O /mm DIAMETER 25 /mm GLUE TAPE	USING FI FRONT MASS DAMPER WITH 3 WEIGHTS 5G UNDER BATTERY. GLUE ON FRONT SIDEWALL.						