

Driver Details

NAME

DATE

EVENT / TRACK

WEATHER

RESULT

FASTEST LAP TIME

Chassis and Electrics

BODYSHELL

WING

E.S.C

SERVO

RECEIVER

LIPO

Track Conditions

GRIP LEVEL

High

Medium

Low

LAYOUT

Tight

Open

Mixed

COMPOSITION

Carpet

Tarmac

SURFACE

Smooth

Bumpy

TEMPERATURE - AIR

°C

°F

 TRACK

°C

°F

VENUE

Indoor

Outdoor

TRACK DIMENSIONS

Motor and Gearing

MOTOR

TIMING

SPUR SIZE

PINION SIZE

Rollout

mm/rev

NOTES



Arr0 - Petitr

Tyres and Additive

COMPOUND

Front

Rear

DIAMETER

Front

Rear

TYRE ADDITIVE

ADDITIVE TIME

Front

Minutes

Rear

Minutes

ADDITIVE COVERAGE

Front

Rear

SIDEWALL GLUE

Front

Rear

Front

Oil

cSt

Ride Height

Spacers

mm

Droop Shims

mm

Ride Height

mm

Droop

mm

Inside wheel lock

°

Toe

°

Spacer

mm

1 Dot

2 Dot

3 Dot

Black

Silver - Kit

Green

Gold

0 Dot - Kit

1 Dot

2 Dot

3 Dot

Middle

1

2

3

4

1

2

3

4

Oil

cSt

Oil

cSt

1 Dot

2 Dot

3 Dot

Black

Silver - Kit

Gold

Nickel

Red Dot

Black Ultra

Plastic - Kit

Alloy

Spacer

mm

Rear

Spacer

mm

Spacer

mm

Width

mm

Ride Height

mm

Droop

mm

Antisquat

mm

Kit (4.2mm)

Antisquat

Black

Silver - Kit

Gold

Nickel

Red Dot

Black Ultra

C/F Diff

Steel Diff

Spool Axle

Preload

°

0.00

0.25

0.50

0.75

1.00

1.25

1.50

1.75

0.00

0.25

0.50

0.75

1.00

1.25

1.50

1.75