ECLIPSE SETUP SHEET	TYRES & ADDITIVE		
	,	Front	Rear
DRIVER DETAILS	COMPOUND		
NAME	FOAM DIAMETER	mm	mm
DATE	TYRE ADDITIVE		
EVENT	ADDITIVE TIME	min	mir
LOCATION	ADDITIVE COVERAGE	%	%
RACE RESULT	SIDEWALL GLUE	70	70
QUALIFYING POSITION	LOIDEVVALL OLOL	1	
FASTEST LAP TIME	TOP DESK STIFFNESS A	DJUSTMENT 5	
TRACK CONDITIONS			
GRIP LEVEL High Medium Low			
TYPE Tight Mixed Open	_		
SURFACE Asphalt Carpet C	_		.
CONDITION Smooth ☐ Bumpy ☐		MIDDLE POSTS	\degree 💄 FRONT POSTS 🗆
TRACK DIMENSIONS			
TEMPERATURE °C °F	ELECTRONICS & BOI	OVSHELL	
MOTOR & GEARING	1		
	BODYSHELL		HEIGHT mn
MOTOR	FRONT PIN HEIGHT Botton		3 4 Top
MOTOR OPTIONS	FRONT HANGERS		OT 3DOT
ROTOR DIAMETER	REAR HANGERS	1DOT ☐ 2D	OOT 3DOT
TIMING	E.S.C		
SPUR GEAR SIZE	SERVO		
PINION SIZE	RECEIVER		
ROLLOUT mm / rev	D.4. T.T.E.D.V		
FRONT			
CAMPED 0.75° 15° 1		FRONT S	DDINGS
		70	
RIDE HEIGHT mm BLAC			.ACK - SOFT LVER - MEDIUM
I OE SILVI	=R		OLD - HARD
DAMPING cSt			HITE - ULTRA
DROOP mm			
CASTER WASHER A (REAR) mm ANGLE SHIMS	mm		
WASHER B (FRONT) mm			
SIL'			
REAR			
RIDE HEIGHT mm	175 150	25 100 0.75	0.50
ROLL DAMPING cSt			
BUMP DAMPING cst			
DROOP mm			
ANTI SQUAT KIT			
	000 SZO 030	92.0	091 941
PIVOT LENGHT LONG SHORT ☐			
	ROLL SPRING	SS (SIDE):	
	BUMP SPRIN	G (CENTRE):	
¦ └- SPACERS mm/side ┘	SOFTER		HARDER
	U4838 BLAC	K - U4839 SILVER - U4840 (GOLD - U4841 NICKEL
LTRACK WIDTH mm			

Alterations: Arn0 / PetitRC.com