

Setup Sheet

DRIVER DETAILS

NAME

DATE

EVENT

LOCATION

RACE RESULT

QUALIFYING POSITION

FASTEST LAP TIME

TRACK CONDITIONS

GRIP LEVEL

High ☐

Medium ☐

Low ☐

TYPE

Tight ☐

Mixed ☐

Open ☐

SURFACE

CONDITION

Smooth ☐

Bumpy ☐

TRACK DIMENSIONS

TEMPERATURE

°C

°F

MOTOR & GEARING

MOTOR

MOTOR OPTIONS

ROTOR DIAMETER

TIMING

SPUR GEAR SIZE

PINION SIZE

ROLLOUT

mm / rev

NOTES

TYRES & ADDITIVE

	Front	Rear
COMPOUND		
FOAM DIAMETER	mm	mm
TYRE ADDITIVE		
ADDITIVE TIME	min	min
ADDITIVE COVERAGE	%	%
SIDEWALL GLUE		

ELECTRICS & BODYSHELL

BODYSHELL	HEIGHT	mm
E.S.C		
SERVO		
RECEIVER		
LiPo		

FRONT

CAMBER	degrees
RIDE HEIGHT	mm
RIDE HEIGHT SPACER	1.0mm ☐ 1.5mm ☐ 2mm ☐
TOE OUT	degrees/side
DAMPING	cSt
DROOP	mm
FRONT END BRACE	O-ring ☐ Solid ☐ Removed ☐

REACTIVE CASTER

5° ☐

10° ☐

SPACER.....mm

SHIMS.....mm

SHIMS.....mm

SHIMS.....mm

STATIC CASTER

FRONT	REAR	STATIC CASTER
1.5mm	0mm	2.5°
1mm	0.5mm	4.0° (kit)
0.5mm	1mm	6.0°
0mm	1.5mm	7.5°

UPPER ARM LENGTH

SPACER.....mm

FRONT TRACK WIDTH

☐ -0.5mm

☐ 0.0mm

☐ +0.5mm

OUTBOARD

SHIMS.....mm

INBOARD

FRONT SPRINGS

☐ SUPER SOFT - U7013

☐ RED - U7015

☐ YELLOW - U7016

☐ BLUE - U7014

☐ SOFT - U7012

☐ MEDIUM SOFT - U7011

☐ MEDIUM - U7009

☐ HARD - U7010

REAR

RIDE HEIGHT	mm
ROLL DAMPING	cSt
BUMP DAMPING	cSt
DROOP	mm
ROLL CENTRE SHIFT	KIT ☐ +2.5mm ☐ mm ☐
ANTI SQUAT	KIT ☐ ANTI SQUAT ☐
DIFF PRELOAD	360° KIT ☐ ° ☐

175

150

125

100

0.75

0.50

0.25

0.00

0.20

0.50

0.75

1.00

1.20

1.50

1.75

SPACERS.....mm/side

TRACK WIDTH.....mm

ROLL SPRINGS (SIDE)

SOFTER

HARDER

U4838 BLACK ☐

U4839 SILVER ☐

U4840 GOLD ☐

U4841 NICKEL ☐

BUMP SPRING (CENTRE)

SOFTER

HARDER

U4838 BLACK ☐

U4839 SILVER ☐

U4840 GOLD ☐

U4841 NICKEL ☐