

DRIVER DETAILS

NAME Robert Krens
 DATE 03-09-2017
 EVENT CW#5 HFCL
 WEATHER Dry, Sunny, 22degC
 RESULT TQ + Win
 FASTEST LAP TIME 17.439

CHASSIS AND ELECTRICS

CHASSIS Alloy ☐ Carbon ☒
 TOP DECK 2.0mm ☒ 2.5mm ☐ 3.0mm ☐ 4.0mm ☐
 BODYSHELL Protoform LTC-R LW
 WING JG Racing Wing, 10mm overhang
 E.S.C Much More Fleta Euro's
 SERVO Futaba 9551
 RECEIVER Sanwa 451R
 CELLS Basher 6600Mah 7.6V

TRACK CONDITIONS

GRIP LEVEL High ☐ Medium ☒ Low ☐
 TYPE Tight ☒ Open ☐ Mixed ☐
 SURFACE Carpet ☐ Tarmac ☒
 CONDITION Smooth ☐ Bumpy ☒
 TEMPERATURE 35 °C °F
 VENUE Indoor ☐ Outdoor ☒

NOTES

Antidive and Armsweep give great feeling an corner speed.
 Raised rear rollcenter (sup's arms) and gone from 1.5 toe to 2.0 which gave beter exit speed and "rip" out of the corner yet more cornerspeed. Perthiperal dampers made the car a bit easier on cerbstones and give a bit less steering.
 0.5mm shim front and rear at hubs. Body 14mm forward mounted. Car is just simply awesome.



MOTOR AND GEARING

MOTOR Much More Fleta 13.5T ZW
 ROTOR DIAMETER 12.3mm
 TIMING "Fixed" 12deg
 GEAR PITCH 48DP ☐ 64DP ☒
 SPUR SIZE 16
 PINION SIZE 38

WHEELS, TYRES AND INSERTS

WHEELS Sorex
 TYRES Sorex 32R
 INSERTS BRCA Yellow
 TYRE ADDITIVE MR33 + LG1 (4/1)
 ADDITIVE TIME Front 20 Minutes Rear 20 Minutes
 TYRE WARMERS Yes ☒ No ☐ Temp 65 °C Time 20 Minutes

FRONT

Diff Oil cTs

Washers 1.5mm
 Washers1.5mm

4° R ☒ 4° Yoke ☐ 6° Yoke ☐
 Yes ☐ No ☐
 SERVO SAVER

Alloy ☐ Steel ☐ Double Joint ☒

Washers 0.5mm

1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm

Washers 1.0mm

12mm ☐
 13mm ☐
 14mm ☐

Washers 1.0mm

Narrow ☐
 Medium (kit) ☒

0.2mm
 2.0mm

Line In ☐
 Line Out ☒

Shims 0.5mm

Washersmm

Droop 1.5mm
 On 10mm Block ☐
 Ride Height 5.6mm
 Camber 2.2°
 Toe 1.0°
 Pivot Block Strap ☐

44.2 (b)mm
 43.5 ☐ 44.2 ☒ 46.0 ☐

Cap Type Vented ☒ Sealed ☐ Emulsion ☐
 Oil 500cTs
 Spring Schumi Green
 no holes
 Piston no holes
 Drilled Yes ☐ No ☒
 Drilled piston Hole Sizemm
 Shock Length (X)mm
 Rebound 0%

Peripheral Damping
 Yes ☒
 No ☐

REAR

Diff Oil 2000 cTs

Washers 1.2mm

Alloy ☒ Steel ☐

Washersmm

WheelBase
 Short ☐
 Middle ☐
 Long ☐

0 Groove
 1 Groove
 2 Groove

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm

Medium ☐
 Wide (kit) ☒

Droop 2.8mm
 On 10mm Block ☐
 Ride Height 5.8mm
 Camber 1.8°
 Pivot Block Strap ☐

Line In ☐
 Line Out ☒

Washers 1.5mm

44.2 ☐ 45.5 ☐ 46.1 ☐

Shims 1.0mm

Cap Type Vented ☒ Sealed ☐ Emulsion ☐
 Oil 500cTs
 Spring Schumi Green
 no holes
 Piston no holes
 Drilled Yes ☐ No ☒
 Drilled piston Hole Sizemm
 Shock Length (X)mm
 Rebound 0%

Peripheral Damping
 Yes ☐
 No ☒