

DRIVER DETAILS

NAME
DATE
EVENT
WEATHER
RESULT
FASTEST LAP TIME

CHASSIS AND ELECTRICS

CHASSIS Alloy ☐ Carbon ☐
TOP DECK 2.0mm ☐ 2.5mm ☐ 3.0mm ☐ 4.0mm ☐
BODYSHELL
WING
E.S.C
SERVO
RECEIVER
CELLS

TRACK CONDITIONS

GRIP LEVEL High ☐ Medium ☐ Low ☐
TYPE Tight ☐ Open ☐ Mixed ☐
SURFACE Carpet ☐ Tarmac ☐
CONDITION Smooth ☐ Bumpy ☐
TEMPERATURE °C °F
VENUE Indoor ☐ Outdoor ☐

NOTES



MOTOR AND GEARING

MOTOR
ROTOR DIAMETER
TIMING
GEAR PITCH 48DP ☐ 64DP ☐
SPUR SIZE
PINION SIZE

WHEELS, TYRES AND INSERTS

WHEELS
TYRES
INSERTS
TYRE ADDITIVE
ADDITIVE TIME Front Minutes Rear Minutes
TYRE WARMERS Yes ☐ No ☐ Temp °C Time Minutes

FRONT

☐ Spool
☐ Gear Diff
Diff Oil cTs

☐ 1 Dot - 1.1mm
☐ 2 Dot - 1.2mm
☐ 3 Dot - 1.3mm
☐ 4 Dot - 1.4mm
☐ 5 Dot - 1.5mm

Washersmm
Line In ☐ Shimsmm
Line Out ☐ Shimsmm

Drop.....mm
On 10mm Block ☐
Ride Heightmm
Camber.....°
Toe.....°
Pivot Block Strap ☐
43.5 ☐ 44.2 ☐ 46.0

Washersmm
Washers.....mm

Washersmm
12mm ☐
13mm ☐
14mm ☐

4° R ☐ 6° Yoke
SERVO SAVER Yes ☐ No ☐

Alloy ☐ Steel ☐ Double Joint ☐

Narrow ☐ Medium (kit) ☐
Washersmm

Cap Type Vented ☐ Sealed ☐ Emulsion ☐
Oil.....cTs
Spring.....
Piston.....
Drilled Yes ☐ No ☐
Drilled piston Hole Size.....mm
Shock Length (X).....mm
Rebound%

Peripheral Damping Yes ☐ No ☐

REAR

Diff Oil cTs

☐ 0 Dot - 1.0mm
☐ 1 Dot - 1.1mm
☐ 2 Dot - 1.2mm
☐ 3 Dot - 1.3mm
☐ 4 Dot - 1.4mm

☐ Medium
☐ Wide (kit)

Drop.....mm
On 10mm Block ☐
Ride Heightmm
Camber.....°
Pivot Block Strap ☐
44.2 ☐ 45.5 ☐ 46.1

Washersmm
Washers.....mm

Washersmm
WheelBase ☐ Short ☐ Middle ☐ Long ☐

Alloy ☐ Steel ☐

(2 Pip shown)
☐ 0 Groove
☐ 1 Groove
☐ 2 Groove

Shims.....mm
Shims.....mm

Cap Type Vented ☐ Sealed ☐ Emulsion ☐
Oil.....cTs
Spring.....
Piston.....
Drilled Yes ☐ No ☐
Drilled piston Hole Size.....mm
Shock Length (X).....mm
Rebound%

Peripheral Damping Yes ☐ No ☐