

## DRIVER DETAILS

NAME  
DATE  
EVENT  
WEATHER  
RESULT  
FASTEST LAP TIME

## CHASSIS AND ELECTRICS

CHASSIS Alloy ☐ Carbon ☐  
TOP DECK 2.0mm ☐ 2.5mm ☐ 3.0mm ☐ 4.0mm ☐  
BODYSHELL  
WING  
E.S.C  
SERVO  
RECEIVER  
CELLS

## TRACK CONDITIONS

GRIP LEVEL High ☐ Medium ☐ Low ☐  
TYPE Tight ☐ Open ☐ Mixed ☐  
SURFACE Carpet ☐ Tarmac ☐  
CONDITION Smooth ☐ Bumpy ☐  
TEMPERATURE °C °F  
VENUE Indoor ☐ Outdoor ☐

## NOTES



## MOTOR AND GEARING

MOTOR  
ROTOR DIAMETER  
TIMING  
GEAR PITCH 48DP ☐ 64DP ☐  
SPUR SIZE  
PINION SIZE

## WHEELS, TYRES AND INSERTS

WHEELS  
TYRES  
INSERTS  
TYRE ADDITIVE  
ADDITIVE TIME Front Minutes Rear Minutes  
TYRE WARMERS Yes ☐ No ☐ Temp °C Time Minutes

## FRONT

☐ Spool  
☐ Gear Diff  
Diff Oil ..... cTs

☐ 1 Dot - 1.1mm  
☐ 2 Dot - 1.2mm  
☐ 3 Dot - 1.3mm  
☐ 4 Dot - 1.4mm  
☐ 5 Dot - 1.5mm

Washers .....mm  
Line In ☐ Shims .....mm  
Line Out ☐ Shims .....mm

Drop .....mm  
On 10mm Block ☐  
Ride Height .....mm  
Camber .....°  
Toe .....°  
Pivot Block Strap ☐  
43.5 ☐ 44.2 ☐ 46.0

4° R ☐ 6° Yoke  
SERVO SAVER Yes ☐ No ☐

Washers .....mm  
12mm ☐  
13mm ☐  
14mm ☐

Cap Type Vented ☐ Sealed ☐ Emulsion ☐  
Oil .....cTs  
Spring .....  
Piston .....  
Drilled Yes ☐ No ☐  
Drilled piston Hole Size .....mm  
Shock Length (X) .....mm  
Rebound .....%

Alloy ☐ Steel ☐ Double Joint ☐  
Narrow ☐ Medium (kit) ☐  
Washers .....mm

## REAR

Diff Oil ..... cTs

☐ 0 Dot - 1.0mm  
☐ 1 Dot - 1.1mm  
☐ 2 Dot - 1.2mm  
☐ 3 Dot - 1.3mm  
☐ 4 Dot - 1.4mm

☐ Medium  
☐ Wide (kit)

Drop .....mm  
On 10mm Block ☐  
Ride Height .....mm  
Camber .....°  
Pivot Block Strap ☐  
44.2 ☐ 45.5 ☐ 46.1

0 Groove ☐ 1 Groove ☐ 2 Groove ☐  
(2 Pip shown)

Washers .....mm  
WheelBase ☐ Short ☐ Middle ☐ Long ☐

Cap Type Vented ☐ Sealed ☐ Emulsion ☐  
Oil .....cTs  
Spring .....  
Piston .....  
Drilled Yes ☐ No ☐  
Drilled piston Hole Size .....mm  
Shock Length (X) .....mm  
Rebound .....%

Alloy ☐ Steel ☐  
Washers .....mm