

**Driver Details**

NAME \_\_\_\_\_

DATE \_\_\_\_\_

EVENT / TRACK \_\_\_\_\_

WEATHER \_\_\_\_\_

RESULT \_\_\_\_\_

FASTEST LAP TIME \_\_\_\_\_

**Notes**

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_



**Chassis and Electrics**

CHASSIS Mid  Alloy  Carbon

TOP DECK Vertical  Horizontal

BODYSHELL \_\_\_\_\_

WING \_\_\_\_\_

E.S.C \_\_\_\_\_

SERVO \_\_\_\_\_

RECEIVER \_\_\_\_\_

LIPO \_\_\_\_\_

**Wheels, Tyres and Inserts**

WHEELS \_\_\_\_\_

TYRES \_\_\_\_\_

INSERTS \_\_\_\_\_

TYRE ADDITIVE \_\_\_\_\_

|               |                              |                             |         |              |
|---------------|------------------------------|-----------------------------|---------|--------------|
| ADDITIVE TIME | Front                        | Minutes                     | Rear    | Minutes      |
| TYRE WARMERS  | Yes <input type="checkbox"/> | No <input type="checkbox"/> | Temp °C | Time Minutes |

**Track Conditions**

GRIP LEVEL High  Medium  Low

TYPE Tight  Open  Mixed

SURFACE Carpet  Tarmac

CONDITION Smooth  Bumpy

TEMPERATURE Air °C °F Track °C °F

VENUE Indoor  Outdoor

**Topdeck Options**

Topdeck Posts \_\_\_\_\_

Topdeck Posts \_\_\_\_\_

Anti-lozenge Motor mount  Servo mount

Topdeck Cuts \_\_\_\_\_

Raised  .....mm

**Motor and Gearing**

MOTOR \_\_\_\_\_

ROTOR DIAMETER \_\_\_\_\_

TIMING \_\_\_\_\_

GEAR PITCH 48DP  64DP

SPUR SIZE \_\_\_\_\_

PINION SIZE \_\_\_\_\_

**Front**

Spool  
 Gear Diff  
Diff Oil ..... cTs

Washers .....mm

SERVO SAVER Yes  No

Washers .....mm

Strap  Split Block

Washers .....mm

Washers .....mm

No Dot - 1.0mm  
 1 Dot - 1.1mm  
 2 Dot - 1.2mm - Kit  
 3 Dot - 1.3mm

53.0mm  
 53.5mm  
 54.5mm - Kit

0 Dot - Kit  
 1 Dot Front Hole  
 1 Dot Rear Hole

2 Dot  
 3 Dot Front Hole  
 3 Dot Rear Hole

Peripheral Damping Yes  No

Cap Type Vented  Sealed  Emulsion

Oil .....cTs

Diff Oil ..... cTs

Washers .....mm

Inside Wheel Lock .....°

Outside Wheel Lock .....°

Washers .....mm

Drop .....mm (on 1.6mm droop gauge spacer) Pivot Pin Insert

Ride Height .....mm

Camber .....°

Toe .....°

Shims .....mm

Shims .....mm

Spring .....mm

Piston .....mm

Drilled Yes  No

Drilled piston Hole Size .....mm

Shock Length (X) .....mm

Rebound .....%

**Rear**

Diff Oil ..... cTs

No Dot - 1.0mm  
 1 Dot - 1.1mm  
 2 Dot - 1.2mm - Kit  
 3 Dot - 1.3mm

Washers .....mm

Washers .....mm

Washers .....mm

Motor Screw Positions

Washers .....mm

Washers .....mm

53.0mm - Kit  
 53.5mm  
 54.5mm

0 Dot - Kit  
 1 Dot Front Hole  
 1 Dot Rear Hole

2 Dot  
 3 Dot Front Hole  
 3 Dot Rear Hole

Peripheral Damping Yes  No

Cap Type Vented  Sealed  Emulsion

Oil .....cTs

Diff Oil ..... cTs

Washers .....mm

Washers .....mm

Drop .....mm (on 1.6mm droop gauge spacer) Pivot Pin Insert

Ride Height .....mm

Camber .....°

Toe .....°

Shims .....mm

Shims .....mm

Spring .....mm

Piston .....mm

Drilled Yes  No

Drilled piston Hole Size .....mm

Shock Length (X) .....mm

Rebound .....%