

Driver Details		Notes																
NAME <i>Marcos FJ</i>		<i>outdoor covered track</i> Mi7																
DATE																		
EVENT / TRACK <i>SS Raceway</i>																		
WEATHER <i>clear</i>																		
RESULT																		
FASTEST LAP TIME <i>10.9</i>																		
Chassis and Electrics																		
CHASSIS <i>Rear motor</i>		☐ Mid ☐ Alloy ☒ Carbon																
TOP DECK		☐ Vertical ☒ Horizontal																
BODYSHELL <i>ZooRacing HellCat</i>																		
WING <i>Stock</i>																		
E.S.C <i>HobbyWing</i>																		
SERVO <i>Team Powers</i>																		
RECEIVER <i>Sanwa</i>																		
LIPO <i>Trinity White Carbon LCG</i>																		
Track Conditions																		
GRIP LEVEL	High ☐ Medium ☒ Low ☐																	
TYPE	Tight ☐ Open ☐ Mixed ☒																	
SURFACE	Carpet ☐ Tarmac ☒																	
CONDITION	Smooth ☒ Bumpy ☐																	
TEMPERATURE	Air °C 98°F Track 95 °C °F																	
VENUE	Indoor ☐ Outdoor ☐																	
Motor and Gearing																		
MOTOR <i>Trinity Revtech 5.5</i>																		
ROTOR DIAMETER <i>stock</i>																		
TIMING <i>25degrees</i>																		
GEAR PITCH 48DP ☒ 64DP ☐																		
SPUR SIZE <i>84</i>																		
PINION SIZE <i>21</i>																		
Wheels, Tyres and Inserts																		
WHEELS <i>Volante</i>																		
TYRES <i>36</i>																		
INSERTS <i>premount</i>																		
TYRE ADDITIVE <i>mighty gripper yellow</i>																		
ADDITIVE TIME Front 10Minutes Rear 10Minutes																		
TYRE WARMERS Yes ☐ No ☒ Temp °C Time Minutes																		
Topdeck Options																		
Topdeck Posts Topdeck Posts ☐ Anti-lozenge ☐ Motor mount ☐ Servo mount Topdeck Cuts Raised ☐mm																		
Front																		
☐ Spool ☒ Gear Diff Diff OilcTs	SERVO SAVER ☐ Yes ☐ No	Washers1 mm ☐ Strap ☐ Split Block	Washers1.5 mm Washers1 mm ☐ No Dot - 1.0mm ☒ 1 Dot - 1.1mm ☒ 2 Dot - 1.2mm - Kit ☐ 3 Dot - 1.3mm															
☐ Narrow ☒ Medium (kit) ☐ Wide	Washers1 mm Inside Wheel Lock28° Outside Wheel Lock°	☐ 53.0mm ☐ 53.5mm ☒ 54.5mm - Kit	☒ 0 Dot - Kit ☐ 2 Dot ☐ 1 Dot Front Hole ☐ 3 Dot Front Hole ☐ 1 Dot Rear Hole ☐ 3 Dot Rear Hole															
☐ No Dot - 1.0mm ☒ 1 Dot - 1.1mm ☒ 2 Dot - 1.2mm - Kit ☐ 3 Dot - 1.3mm Washers1 mm Droop6 mm (on 1.6mm droop gauge spacer) Ride Height5.2 mm Camber2° Toe1.5° Shims5 mm Shims5 mm <table border="1" style="font-size: 0.8em;"> <thead> <tr> <th></th> <th>Front</th> <th>Rear</th> </tr> </thead> <tbody> <tr> <td>0.25 In</td> <td>☒</td> <td>☒</td> </tr> <tr> <td>0.25 Out</td> <td>☐</td> <td>☐</td> </tr> <tr> <td>0.75 In</td> <td>☐</td> <td>☐</td> </tr> <tr> <td>0.75 Out</td> <td>☐</td> <td>☐</td> </tr> </tbody> </table>					Front	Rear	0.25 In	☒	☒	0.25 Out	☐	☐	0.75 In	☐	☐	0.75 Out	☐	☐
	Front	Rear																
0.25 In	☒	☒																
0.25 Out	☐	☐																
0.75 In	☐	☐																
0.75 Out	☐	☐																
Rear																		
Diff Oil7000 cTs	Washers0 mm Washers2 mm Washers0 mm	☒ 53.0mm - Kit ☐ 53.5mm ☐ 54.5mm	☒ 0 Dot - Kit ☐ 2 Dot ☐ 1 Dot Front Hole ☐ 3 Dot Front Hole ☐ 1 Dot Rear Hole ☐ 3 Dot Rear Hole															
☐ No Dot - 1.0mm ☒ 1 Dot - 1.1mm ☒ 2 Dot - 1.2mm - Kit ☐ 3 Dot - 1.3mm	Motor Screw Positions ☒ ☒ ☒	Washers1 mm Droop5 mm (on 1.6mm droop gauge spacer) Ride Height5.4 mm Camber2° Toe3° Shims1 mm Shims1 mm	☐ 53.0mm - Kit ☐ 53.5mm ☐ 54.5mm															
☐ Narrow ☒ Medium (kit) ☐ Wide Washers5 mm Washers5 mm Washers1.5 mm Shims1 mm Shims1 mm <table border="1" style="font-size: 0.8em;"> <thead> <tr> <th></th> <th>Front</th> <th>Rear</th> </tr> </thead> <tbody> <tr> <td>0.25 In</td> <td>☐</td> <td>☐</td> </tr> <tr> <td>0.25 Out</td> <td>☐</td> <td>☐</td> </tr> <tr> <td>0.75 In</td> <td>☒</td> <td>☒</td> </tr> <tr> <td>0.75 Out</td> <td>☐</td> <td>☐</td> </tr> </tbody> </table>					Front	Rear	0.25 In	☐	☐	0.25 Out	☐	☐	0.75 In	☒	☒	0.75 Out	☐	☐
	Front	Rear																
0.25 In	☐	☐																
0.25 Out	☐	☐																
0.75 In	☒	☒																
0.75 Out	☐	☐																
☐ No Dot - 1.0mm ☒ 1 Dot - 1.1mm ☒ 2 Dot - 1.2mm - Kit ☐ 3 Dot - 1.3mm Washers1 mm Droop5 mm (on 1.6mm droop gauge spacer) Ride Height5.4 mm Camber2° Toe3° Shims1 mm Shims1 mm <table border="1" style="font-size: 0.8em;"> <thead> <tr> <th></th> <th>Front</th> <th>Rear</th> </tr> </thead> <tbody> <tr> <td>0.25 In</td> <td>☐</td> <td>☐</td> </tr> <tr> <td>0.25 Out</td> <td>☐</td> <td>☐</td> </tr> <tr> <td>0.75 In</td> <td>☒</td> <td>☒</td> </tr> <tr> <td>0.75 Out</td> <td>☐</td> <td>☐</td> </tr> </tbody> </table>					Front	Rear	0.25 In	☐	☐	0.25 Out	☐	☐	0.75 In	☒	☒	0.75 Out	☐	☐
	Front	Rear																
0.25 In	☐	☐																
0.25 Out	☐	☐																
0.75 In	☒	☒																
0.75 Out	☐	☐																