

Driver Details

Name Andy Sawyer
Date 13/6/21
Event / Track Stafford TORC
Weather Hot
Result
Fastest Lap 18.2

Chassis and Electrics

Chassis Kit ☒ C/F ☐
Top Deck Kit ☐ C/F ☐ Dowel Yes ☐ No ☐
Bodyshell Montech GT1 Vision
Wing kit
ESC Arrowmax Dash AI Pro V2
Servo KO Grasper 2 BSx4S
Receiver KO KR420XT
LiPo IP5000 Under LiPo Weight g

Track Conditions

Grip Level High ☐ Medium ☐ Low ☐
Type Tight ☐ Open ☐ Mixed ☐
Surface Carpet ☐ Tarmac ☐
Condition Smooth ☐ Bumpy ☐
Air Temperature 28 °C °F Track Temperature °C °F
Venue Indoor ☐ Outdoor ☐

Motor and Gearing

Motor Phantom 17.5
Rotor Diameter kit
Timing 45
Gear Pitch 48DP ☐ 64DP ☐
Spur Size 96
Pinion Size 46

Notes

MISSION FT
FRONT WHEEL DRIVE

Mi5 Alloy medium hex - rear
Mi5 Alloy wide hex - front

25g in front bumper
10g at rear of chassis

rear top deck screws loose by 1 turn, allow rear chassis flex









Option Builds

4WD Conversion Yes ☐ No ☐
Body Posts Horizontal ☐ Vertical ☐









Wheels, Tyres and Inserts

Wheels Sweep
Tyres 34
Inserts kit
Tyre Additive MR33 red
Additive Time Front 20 Minutes Rear 20 Minutes
Tyre Warmers Yes ☐ No ☐ Temp 40 °C Time 20 Minutes

Front

 Servo Saver Yes ☐ No ☐ Spool ☐ Gear Diff ☐ Diff Oil...300.000.....cSt	 Inside wheel lock..... Outside wheel lock.....	 ↑ Forward Caster Kwik clips rearward ☐ Kwik clip either side ☐ Kwik clips forward ☐ Bump Steer Washers...0.5.....mm Washers...0.....mm	 Wheelbase Short (Kit) ☐ Long ☐	 Driveshaft Kit ☐ Double Joint ☐
 Washers...0.....mm	 Anti Roll Bar Yes ☐ No ☐	 Plastic ☐ Alloy ☐	 O'Rings...0..... X Ride Height...4.5.....mm Droop...3.....mm Camber...1.....° Toe...0.5 out.....°	 Oil...550.....cSt Spring...Green 16..... Piston...3..... Shock Length (X).....mm Rebound...50.....%

Rear

 None ☐ Gear Diff ☐ Diff Oil.....cSt	 ↑ Forward Wheelbase Short (kwik clips rearward) ☐ Medium (Kit) ☐ Long (kwik clips forward) ☐	 Washers...0.5.....mm Washers...2.....mm	 O'Rings...0..... X	 Ride Height...5.0.....mm Droop...2.0.....mm Camber...1.....° Toe...3.....°
 Washers...0.....mm	 Anti Roll Bar Yes ☐ No ☐	 Inboard Toe 2° (pip facing in) ☐ 0° (pip facing out) ☐ Plastic ☐ Alloy ☐	 Ride Height...5.0.....mm Droop...2.0.....mm Camber...1.....° Toe...3.....°	 Oil...500.....cSt Spring...Black 13..... Piston...3..... Shock Length (X).....mm Rebound...50.....%