



















Driver Details				Notes					
Name Mark Young				<div style="font-size: 2em; font-weight: bold; margin: 0;">MISSION FT</div> <div style="font-size: 0.8em; margin: 0;">FRONT WHEEL DRIVE</div>					
Date 20/032022									
Event / Track WLRC Practice day									
Weather Dry/Cold									
Result 16 307.40									
Fastest Lap 18.74				Mi5 shocks fitted. Ball joint wound out 5mm front 0mm rear. Shock length 2mm longer than droop for front and rear wishbones.					
Chassis and Electrics				Titanium screws and turnbuckles fitted. Carbon shock towers and bumper brace.					
Chassis Kit <input type="checkbox"/> C/F <input type="checkbox"/>				40mm fan in front of motor fixed with purple belt tensioner bracket. 1.5mm rear roll bar.					
Top Deck Kit <input type="checkbox"/> C/F <input type="checkbox"/> Dowel Yes <input type="checkbox"/> No <input type="checkbox"/>									
Bodyshell Blitz MK9 0.7									
Wing Kit									
ESC Hobbywing Justock BRCA control ESC									
Servo SRT									
Receiver Sanwa WP									
LiPo Intellect 4400 Under LiPo Weight 0 g									
Track Conditions				Option Builds					
Grip Level High <input type="checkbox"/> Medium <input type="checkbox"/> Low <input type="checkbox"/>				4WD Conversion Yes <input type="checkbox"/> No <input type="checkbox"/>					
Type Tight <input type="checkbox"/> Open <input type="checkbox"/> Mixed <input type="checkbox"/>				Body Posts Horizontal <input type="checkbox"/> Vertical <input type="checkbox"/>					
Surface Carpet <input type="checkbox"/> Tarmac <input type="checkbox"/>				Wheels, Tyres and Inserts					
Condition Smooth <input type="checkbox"/> Bumpy <input type="checkbox"/>				Wheels Ride BRCA control/ white spoked					
Air Temperature 14 °C °F Track Temperature °C °F				Tyres Ride BRCA control					
Venue Indoor <input type="checkbox"/> Outdoor <input type="checkbox"/>				Inserts Rude BRCA control					
Motor and Gearing				Tyre Additive Spider Red					
Motor Hobbywing 17.5 BRCA control motor				Additive Time Front 15 Minutes Rear 15 Minutes					
Rotor Diameter Kit				Tyre Warmers Yes <input type="checkbox"/> No <input type="checkbox"/> Temp 55 °C Time 15 Minutes					
Timing Fixed									
Gear Pitch 48DP <input type="checkbox"/> 64DP <input type="checkbox"/>									
Spur Size 70T									
Pinion Size 36T									
Front									
 Spool <input type="checkbox"/> Gear Diff <input type="checkbox"/> Diff Oil...500K.....cSt		 Servo Saver Yes <input type="checkbox"/> No <input type="checkbox"/> Inside wheel lock...Max.....° Outside wheel lock.....°		 ↑ Forward Caster Kwik clips rearward <input type="checkbox"/> Kwik clip either side <input type="checkbox"/> Kwik clips forward <input type="checkbox"/>		 Wheelbase Short (Kit) <input type="checkbox"/> Long <input type="checkbox"/>		 Driveshaft Kit <input type="checkbox"/> Double Joint <input type="checkbox"/>	
 Washers...0.....mm		 Anti Roll Bar Yes <input type="checkbox"/> No <input type="checkbox"/>		 Bump Steer Washers...0.....mm Washers...0.....mm Plastic <input type="checkbox"/> Alloy <input type="checkbox"/>		 O'Rings...0..... X Ride Height...5.2..... mm Droop...4.5..... mm Camber...1.5..... ° Toe...0.5..... °		 Oil...475.....cSt Spring...Core RC Grey..... Piston...Kit..... Shock Length (X)...See notes... mm Rebound...25..... %	
Rear									
 None <input type="checkbox"/> Gear Diff <input type="checkbox"/> Diff Oil.....cSt		 ↑ Forward Wheelbase Short (kwik clips rearward) <input type="checkbox"/> Medium (Kit) <input type="checkbox"/> Long (kwik clips forward) <input type="checkbox"/>		 Washers...1.....mm Washers...0.....mm		 Bump Toe			
 Washers...0.....mm		 Inboard Toe 2° (pip facing in) <input type="checkbox"/> 0° (pip facing out) <input type="checkbox"/>		 O'Rings...0..... X Ride Height...5.2..... mm Droop...3.5..... mm Camber...1.5..... ° Toe...2.5..... °		 Oil...350.....cSt Spring...Core RC Blue..... Piston...Kit..... Shock Length (X)...See notes... mm Rebound...25..... %			