

DRIVER AND EVENT DETAILS

Name

Date

Event

Weather

Result

CHASSIS AND ELECTRICS

Chassis

Top Deck ☐ Flex ☐ Standard ☐ Stiff ☐

Bodyshell

Wing

E.S.C

Servo

Receiver

Number of Cells ☐ 4 ☐ 5 ☐ 6 ☐

Type of Cells

TRACK CONDITIONS

Grip Level ☐ High ☐ Medium ☐ Low ☐

Track Type ☐ Tight ☐ Open ☐ Both ☐

Surface ☐ Carpet ☐ Tarmac ☐ Wood ☐

Venue ☐ Indoor ☐ Outdoor ☐

Track Condition ☐ Smooth ☐ Bumpy ☐

Track Temperature °C °F



DRIVER NOTES

MOTOR AND GEARING

Type ☐ Brushed ☐ Brushless ☐

Motor

Brush

Spring

Timing

Gear Pitch ☐ 48Dp ☐ 64Dp ☐

Spur Size

Pinion Size

WHEELS, TYRES AND INSERTS

Wheels

Tyres

Inserts

Tyre Additive

Additive Time MIN (R) MIN (F)

Tyre Warmers ☐ Yes ☐ No ☐

FRONT SETTINGS

Drive ☐ Diff ☐ Spool ☐ One-Way ☐ Height ☐ High ☐ Low ☐

Servo Saver ☐ Yes ☐ No ☐

Toe In-Out ☐ In-board ☐ Out-board ☐ ° Toe-out

Screw Block Spacers Front mm Rear mm

Wishbone Quik-Klips Front mm Rear mm

Link Washers (Horizontal) mm

Ride Height (Chassis to Floor) mm

Droop (Chassis to Floor) mm

Anti-roll Bar ☐ Yes ☐ No ☐ 1.20 ☐ 1.40 ☐ 1.60 ☐



Castor ☐ 0° ☐ 2° ☐ 4° ☐ 6° ☐

Camber ☐ Positive ☐ Negative ☐ Deg

Link Washers (Vertical) mm

Inboard Pin ☐ Kick-up ☐ Anti-dive ☐ Horizontal ☐

Pivot Block Spacers Front mm Rear mm



Front Shocks


Oil WT

Springs


Piston Holes ☐ 2 ☐ 3 ☐

length

Rebound %



Centre Track Rod



REAR SETTINGS

Drive Height ☐ High ☐ Low ☐

Toe In ☐ In-board ☐ Out-board ☐ °

Screw Block Spacers Front mm Rear mm

Wishbone Quik-Klips Front mm Rear mm

Link Washers (Horizontal) mm

Ride Height (Chassis to Floor) mm

Droop (Chassis to Floor) mm



Anti-roll Bar ☐ Yes ☐ No ☐ 1.20 ☐ 1.40 ☐ 1.60 ☐

Camber ☐ Positive ☐ Negative ☐ Deg

Link Washers (Vertical) mm

Inboard Pin ☐ Pro-Squat ☐ Anti-Squat ☐ Horizontal ☐

Pivot Block Spacers Front mm Rear mm



Rear Shocks


Oil WT

Springs

Piston Holes ☐ 2 ☐ 3 ☐

length

Rebound %



Driver Notes