




TRACK CONDITIONS

Type : ☐ Carpet ☒ Asphalt
 Place : ☐ Indoor ☒ Outdoor
 Surface : ☒ Smooth ☐ Med. ☐ Bumpy
 Size: ☐ Open ☐ Med. ☒ Tight
 Traction: ☐ High ☐ Med. ☒ Low
 Track Temp/Air Temp: 20 / 20
 Note: _____



FRONT SUSPENSION

Track Width: _____ mm ☐ Gear Diff _____ wt
 Toe Angle: +0.75 ° ☒ Spool
 Caster: 4 °
 Camber: 1.5 °
 Ride Height: 5.5 mm Anti-Roll Bar: Ø 1.3 mm
 Down Stop: 5.8 mm



REAR SUSPENSION

Track Width: _____ mm Gear Diff 1000 wt
 Toe Angle: _____ °
 Camber: 2 °
 Ride Height: 5.8 mm
 Down Stop: 5.0 mm Anti-Roll Bar: Ø 1.3 mm



ELECTRONICS

Servo: HRC
 ESC: Orion
 Battery: EZ HV

MOTOR

Brand: MuchMore
 Turns: 13.5
 Timing: Fixed

ESC


Punch: max.
 Initial Brake: -
 Drag Brake: -
☐ ESC Timing ☐ Turbo Timing

DRIVE RATIO


Spur 74 T
 Pinion 31 T $\times 1.9 =$ 4.54

TIRES

Insert: Volante 36R
 Wheel: _____
 Shore/deg: _____
 Compound: _____
 Tire Temp: 55
 Tire additive: HRC
 Treated Area



SHOCKS



BODY

