



SETUP SHEET
RS & RS PRO

DRIVER: Tony Newland

VEHICLE: HB D4

TRACK: IRCR Utah

SURFACE: Clay

TRACTION: LOW ☐ MED ☒ HIGH ☐

MOTOR: 10.5

ENDBELL TIMING: 10

ROTOR: stk

GEARING: 22/80

BATTERY: Reedy 4200

ESC SETTINGS:

Firmware
Version: 200

DRAG BRAKE
☒ ☐ ☐ ☐ ☐ ☐ 3

BRAKE STRENGTH
☐ ☐ ☐ ☐ ☒ ☐ 100%

LIMITER
☐ ☐ ☐ ☐ ☒ ☐ none

NEUTRAL WIDTH
☒ ☐ ☐ ☐ ☐ ☐ 3



VOLTAGE CUTOFF
☒ ☐ ☐ ☐ ☐ ☐ 2c

MOTOR TYPE
☐ ☐ ☐ ☐ ☐ ☐ BL/FW

THROTTLE PROFILE
☒ ☐ ☐ ☐ ☐ ☐ 3

HotWire
SOFTWARE 200

DUAL MODE ☐ SENSORED ☒

TIMING ADVANCE: 12

REVERSE STRENGTH:

PUSH CONTROL: off

TIMING BOOST: 12

TURBO BOOST: 100% TURBO DELAY: .5

NOTES:

FILL IN LED LOCATION AND WRITE IN SETTING NUMBER