

SHOCKS POSITION 1 2 3 4 5 6 7 8

SPACER mm

FRONT UPPER BULKHEAD

2 (B-02-G-40362)

SPACER mm

WILD FIRE C-HUB SET VERSION 2 D-05-VBC-0064

WILD FIRE C-HUB SET VERSION 3 D-05-VBC-0166

STEERING BLOCK V2 A-03-VBC-0079

STEERING BLOCK V3 A-03-P30269

SOFT HARD

FRONT SUSPENSION ARM A-03-VBC-0061

V2 FRONT SUSPENSION ARM A-03-VBC-3027

V3 FRONT SUSPENSION ARM A-03-P30267

REAR UPPER BULKHEAD

2 (B-02-G-40362)

SPACER mm

REAR SUSPENSION ARM A-03-VBC-0062

V2 REAR SUSPENSION ARM A-03-VBC-3028

V3 REAR SUSPENSION ARM A-03-P30268

SOFT HARD

REAR UPRIGHT ONE HOLE A03P30178

REAR SUSPENSION UPRIGHT A-03-VBC-0037

FRONT

GROUND CLEARANCE mm DROOP

CAMBER ANGLE ° TOE ANGLE °

CASTER BLOCK ° FRONT DRIVE DIFF (OIL) / DIRECT

STABILIZER 1.2 1.3 1.4 WHEEL SPACER mm

SUSPENSION SHIM (FF) mm SUSPENSION SHIM (FR) mm

SUSPENSION MOUNT (FF) SUSPENSION MOUNT (FR)

AXLE TYPE / SIZE TWO-PIECE JOINT / SINGLE JOINT (STEEL/ALUM) mm

REAR

GROUND CLEARANCE mm DROOP

CAMBER ANGLE ° TOE ANGLE °

REAR DRIVE DIFF (OIL) DRIVE CUP ALUMINUM / STEEL

STABILIZER 1.2 1.3 1.4 WHEEL SPACER mm

SUSPENSION SHIM (RF) mm SUSPENSION SHIM (RR) mm

SUSPENSION MOUNT (RF) SUSPENSION MOUNT (RR)

AXLE TYPE / SIZE TWO-PIECE JOINT / SINGLE JOINT (STEEL/ALUMINUM) mm

FRONT TOE ANGLE

SPACER mm

CENTER STEERING SPACER mm

UPPER DECK mm

STEERING UPRIGHT

BUMP STEER mm

CHASSIS TYPE

NORMAL(FRP)

GRAPHITE

REAR TOE ANGLE

SPACER mm

FRONT

SHOCK LENGTH mm

PISTON 3 4 hole(s) / OTHERS

OIL

SPRING

OIL SEALER CAP S / MS / M / H

REBOUND %

NOTES

MOTOR SPUR T

TIRE TIRE INSERT

TIRE ADDICTIVE BODY

ESC BATTERY

REMARKS

REAR

SHOCK LENGTH mm

PISTON 3 4 hole(s) / OTHERS

OIL

SPRING

OIL SEALER CAP S / MS / M / H

REBOUND %

NOTES

PITCH PINION T

WHEEL

REAR WING

Chassis Flex Settin (Fill in the Circle)