



WHEEL SPACER : 0 mm

UPRIGHT POSITION : ☐ 1 ☒ 2

BATTERY POSITION : ☒ TRANSVERSAL ☐ INLINE

SPACER : 0 mm

ACKERMANN SETTING : ☒ 0mm ☐ 1mm ☐ 2mm ☐ 3mm ☐ 4mm

CASTER SETTING : 264mm ☐ ☒ 268mm

FRONT TOE ANGLE : TOE OUT 1

REAR WING POSITION : ☐ UP ☒ MED ☐ DOWN

SIDE DAMPER TUBE OIL : 10000 CST/WT
10000 CST/WT

DIFF SETTING : ☒ LOOSE ☐
☐
☐
☐ TIGHT

REAR WIDTH : 188 mm

DAMPER SPACER : 2 mm

SIDE DAMPER TUBE SPACER : 0 mm

RIDE HEIGHT : 4.8 mm

SIDE SPRING : H ☐ M ☐ S ☒

OTHERS :

RIDE HEIGHT : 5.0 mm

RIDE HEIGHT : 5.2 mm

SHOCK LENGTH : 64.6 mm

PISTON : 2 ☐ 3 ☒ HOLE(S) / OTHERS

OIL : 350 CST/WT

SPRING : H ☐ M ☐ S ☒ / OTHERS

REBOUND : 20 %

MOTOR : ROTOR : TIMING :

SPUR : PITCH/ T PINION : PITCH/ T ROLLOUT :

ESC : SETUP : BATTERY :

STEERING EXPO : BRAKE E.P. : THROTTLE EXPO :

BODY : WEIGHT :

REMARKS :

FRONT TIRES

TIRE : RIDE

DIAMETER : mm

WHEEL : RIDE

TIRE TREATMENT :

TREATMENT TIME :

SURFACE TREATED :

NOTES :

REAR TIRES

TIRE : RIDE

DIAMETER : mm

WHEEL : RIDE

TIRE TREATMENT :

TREATMENT TIME :

SURFACE TREATED :

NOTES :

AXLE SPACER : ☐ UP ☒ DOWN

CAMBER ANGLE 1.5

ACTIVE CASTER : 0 Deg ☒ 5 Deg ☐

SPACER : 2 mm

SPACER : 3 mm

OTHERS :

SHOCK

REAR AXLE