



DRIVER	DATE
TRACK NAME	RESULT
TRACK SURFACE	GRIP CONDITION HI MED LOW
HUMIDITY	TRACK TEMP

SETUP SHEET




GROUND CLEARANCE	mm	REBOUND	mm
CAMBER ANGLE		TOE ANGLE	•
CASTER BLOCK		FRONT DRIVE DIFF (OIL)	DIRECT
STABILIZER 1.2	3 1.4	WHEEL SPACER	mm
FRONT SUSPENSION MOUI	TSHIM mm	REAR SUSPENSION MOUNT SHIM	mm
FRONT SUSPENSION MOUI	Т	REAR SUSPENSION MOUNT	



REAR

GROUND CLEARANCE	mm	REBOUND		mm
CAMBER ANGLE	۰	TOE ANGLE		
CASTER BLOCK		FRONT DRIVE	DIFF (OIL]
STABILIZER 1.2 1.3	1.4	WHEEL SPACER		mm
FRONT SUSPENSION MOUNT SHIP	M mm	REAR SUSPENSION	ON MOUNT SHIM	mm
FRONT SUSPENSION MOUNT		REAR SUSPENSION MOUNT		



6

FRONT

 SHOCK LENGTH

 PISTON
 1
 2
 3
 hole(s)

 OIL
 SPRING



REAR

 SHOCK LENGTH

 PISTON
 1
 2
 3
 hole(s)

 OIL
 SPRING

