

RESULT

AIR TEMP

SURFACE BUMPY MEDIUM SMOOTH

FrontRear

GROUND CLEARANCE				mm	DROOP		mm
CAMBER ANGLE				°	TOE ANGLE		°
REAR DRIVE	DIFF (OIL)				DRIVE CUP	ALUMINUM / STEEL	
STABILIZER	1.2	1.3	1.4		WHEEL SPACER		mm
SUSPENSION SHIM (FF)				mm	SUSPENSION SHIM (FR)		mm
SUSPENSION MOUNT (FF)					SUSPENSION MOUNT (FR)		
AXLE TYPE / SIZE		TWO-PIECE JOINT / SINGLE JOINT (STEEL/ALUM)				mm	

Front**Rear**

SHOCK LENGTH		mm
PISTON 3 4 hole(s) / OTHERS		
OIL		
SPRING		
OIL SEALER CAP	S / MS / M / H	
REBOUND		%
NOTES		
MOTOR		SPUR
TIRE		TIRE IN
TIRE ADDITIVE		BODY
ESC		BATTE
REMARKS		

SHOCK LENGTH		mm
PISTON 3 4 hole[s] / OTHERS		
OIL		
SPRING		
OIL SEALER CAP	S / MS / M / H	
REBOUND		%
NOTES		
PITCH	PINION	T
WHEEL		
REAR WING		

Chassis Flex Setting (Fill in the Circle)

