

FRONT

C-HUB
 SILVER
 GOLD
 RED

CAMBER
 1.5°

KNUCKLE
 SILVER
 GOLD
 RED

FRONT ARM
 SILVER
 GOLD
 RED

Wheel Hex
 5 mm

SPACER
 0 mm

STABILIZER
 1.3 mm

DIFF OUTER DRIVE
 SOILD AXLE SPRING STEEL
 GEAR DIFF ALUMINIUM
 OIL _____ cst
 POSITION (HIGH/LOW)

SPACER
 2 mm

DIFF OUTER DRIVE
 GEAR DIFF STEEL
 ALUMINIUM
 OIL 3000 cst
 POSITION (HIGH/LOW)

SPACER
 2 mm

STABILIZER
 1.3 mm

Wheel Hex
 5 mm

DOWNSTOP
 5.5 mm

SUSPENSION MOUNT
 SUSPENSION SHIM FF 0 mm
 FR 0 mm
 FF MOUNT BRASS

INSERT
 FR 1 NARROW/WIDE
 FR MOUNT TYPE BRASS
 SOILD
 SPLIT

SUSPENSION MOUNT
 SUSPENSION SHIM RF 0.5 mm
 RR 0.5 mm
 RR MOUNT BRASS

INSERT
 RF 1 NARROW/WIDE
 RF MOUNT TYPE BRASS
 SOILD
 SPLIT

REAR

CAMBER
 2°

SPACER
 2 mm

Wheel Hex
 5 mm

REAR HUB
 SILVER
 GOLD
 RED
 TWO HOLE
 ONE HOLE

REAR ARM
 SILVER
 GOLD
 RED

DOWNSTOP
 1 mm

SPACER
 0 mm

STEERING LOCK

STEERING
 FLOATING
 NON-FLOATING

SERVO HORN
 HEIGHT 19 mm
 BRAND VBC

FLEX
 NONE
 LINKAGE
 CARBON FIBER

WEIGHT
 NONE
 ONE - PIECE
 TWO - PIECE

GROUND CLEARANCE
 5 mm

WHEELBASE SETUP
 FF 1 mm FR 3 mm RF 3 mm RR 1 mm

GROUND CLEARANCE
 5.2 mm

FRONT SHOCK

PISTON 3 (4 hole(s) / OTHERS)

OIL 450

SPRING SMJ SILVER

OIL SEALER CAP CLEAN (BLACK) / BLUE / RED

REBOUND 0 %

NOTES

FRONT ARM
 SILVER
 GOLD
 RED

KNUCKLE
 SILVER
 GOLD
 RED

DOWNSTOP
 UNDER ARM _____ mm

REAR SHOCK

PISTON 3 (4 hole(s) / OTHERS)

OIL 450

SPRING SMJ BLUE

REBOUND 0 %

NOTES

SPACER
 _____ mm

TOE
 BOARD TOE _____
 FINAL TOE _____

C-HUB
 SILVER
 GOLD
 RED
 ALUMINIUM
 CASTER _____

ARTS SETUP
SPACER
 _____ mm
SPACER
 _____ mm
Wheel Hex
 _____ mm

Shocks Shim
 TOWER 2 mm
 ARM 0 mm

WEIGHT
 0 g

CENTERLINE FLEX

UPPERDECK
 1.6mm
 2.0mm

Shocks Shim
 TOWER 0 mm
 ARM 0 mm

WEIGHT
 0 g

CHASSIS
 CARBON
 ALUMINIUM

WEIGHT
 0 g

WEIGHT
 0 g

SPACER
 0 mm

MOTOR	SPUR	PITCH/	T	PINION	PITCH/	T
TIRE	TIRE INSERT		WHEEL			
TIRE ADDICTIVE	BODY		REAR WING			
ESC	BATTERY					
REMARKS						