WILDFIRE 009

1/10 4WD ELECTRIC COMPETITION TOURING CAR KIT

ArnO / PetitRC

SETUP SHEET

DRIVER Xavier | DATE 14/02/18 | EVENT saison 17

TRACK Thionville | GRIP HI / MED / LOW | TRACK TEMP | HUMIDITY

COMPOSITION ASPHALT (INDOOR/OUTDOOR) CARPET | SURFACE BUMPY/SMOOTH | LAYOUT OPEN/MIXED/TIGHT

RESULT | BEST LAP

FRONT

CAMBER 0°

C-HUB: SILVER / GOLD / RED

KNUCKLE: SILVER / GOLD / RED

FRONT ARM: SILVER / GOLD / RED

WHEEL HEX 5 mm

DIFF — OUTER DRIVE: SOLID AXLE / GEAR DIFF; SPRING STEEL / ALUMINIUM / PLASTIC

OIL ___ cst

POSITION HIGH / LOW

SPACER 2 mm

SPACER 0 mm

STABILIZER 1.3 mm

DOWNSTOP: 6.6 6.4 6.2 6.0 5.8 5.6 5 — Default

UNDER ARM centre axe 10 mm

SUSPENSION MOUNT

SUSPENSION SHIM		INSERT	
FF	0 mm	FF 1	NARROW/WIDE
FR	0 mm	FR 1	NARROW/WIDE

FF MOUNT: BRASS

FR MOUNT TYPE: BRASS / SOLID / SPLIT

REAR

DIFF — OUTER DRIVE: GEAR DIFF; STEEL / ALUMINIUM

OIL 1000 cst

POSITION HIGH / LOW

SPACER 2 mm

STABILIZER 1.3 mm

CAMBER 2°

SPACER 2 mm

WHEEL HEX 5 mm

REAR HUB: SILVER / GOLD / RED / TWO HOLE / ONE HOLE

REAR ARM: SILVER / GOLD / RED

DOWNSTOP: 1.0 1.2 1.4 1.6 1.8 2.0 — Default

UNDER HUB/ARM centre axe 8 mm

SUSPENSION MOUNT

SUSPENSION SHIM		INSERT	
RF	0.5 mm	RF 1	NARROW/WIDE
RR	0.5 mm	RR 2	NARROW/WIDE

RR MOUNT: BRASS

RF MOUNT TYPE: BRASS / SOLID / SPLIT

CENTER

SPACER 0 mm

STEERING LOCK

STEERING: FLOATING / NON-FLOATING

SERVO HORN — HEIGHT 20 mm — BRAND

FLEX: NONE / LINKAGE / CARBON FIBER

WEIGHT: NONE / ONE - PIECE / TWO - PIECE

GROUND CLEARANCE 5.0 mm

WHEELBASE SETUP

FF	FR	RF	RR
3 mm	1 mm	2 mm	2 mm

GROUND CLEARANCE 6.0 mm

FRONT SHOCK

PISTON 3 hole(s)

OIL YOK 450

SPRING SMJ Silver

SEALER CAP: CLEAR / BLACK / BLUE / RED

REBOUND 0 %

REAR SHOCK

PISTON 3 hole(s)

OIL YOK 450

SPRING SMJ Silver

SEALER CAP: CLEAR / BLACK / BLUE / RED

REBOUND 0 %

SHOCKS SHIM — TOWER 2 mm — ARM 0 mm

CENTERLINE FLEX: 1 2 3 4 5

SHOCKS SHIM — TOWER 0 mm — ARM 0 mm

WEIGHT ___ g

UPPER DECK: 1.6mm / 2.0mm

WEIGHT ___ g

WEIGHT ___ g

CHASSIS: CARBON / ALUMINIUM

WEIGHT ___ g

SPACER 0 mm

ARTS SETUP

SPACER ___ mm

TOE — BOARD TOE ___ — FINAL TOE ___

C-HUB: SILVER / GOLD / RED / ALUMINIUM — CASTER ___

SPACER ___ mm

SPACER ___ mm

WHEEL HEX ___ mm

SPACER ___ mm

FRONT ARM: SILVER / GOLD / RED

KNUCKLE: SILVER / GOLD / RED

DOWNSTOP: 4.0 4.2 4.4 4.6 4.8 5.0 5.2

UNDER ARM ___ mm

MOTOR LRP 10.5T 37.5° | SPUR 78 T | PINION 33 T | PITCH 48

TIRE LRP 36 | INSERT STD | WHEEL STD

TIRE ADDITIVE LRP Asphalt | BODY Mazda 6 | REAR WING STD

ESC LRP FLOW comp blinky | BATTERY LRP 5600 110C