



VIPER VTX SERIES SETUP SHEET

WHO & WHERE

DRIVER: Youhei Fujioka(FuZy)

TRACK: ABC EP OFF-road Tr.(Hyogo,JPN)

☐ TIGHT ☐ MIXED ☒ OPEN

CLASS: ☐ ONROAD ☒ OFF ROAD ☐ DRIFT

TRACTION: ☒ L ☐ M ☐ H

EVENT: At Practice

DATE: 06/29/2013

CAR & ELECTRONICS

VEHICLE: TAMIYA TRF502X

MOTOR: VST 7.5T

TIMING: Initial Value

FDR:

ESC: ☐ VTX10 ☐ VTX10R ☐ VTX1
☐ VTX10-BE ☒ VTX10R-BE ☐ VTX8

BATTERY: EnRoute 4200mAh 30C

SERVO: SANWA ERS-951

SPEED CONTROLLER SETTING

BRAKE

STRENGTH: 100 %

PWM FREQUENCY: 12000 Hz

CURVE: Linear

THROTTLE

PWM FREQUENCY: 9600 Hz

PUNCH: 100 %

CURVE: Linear

DEAD BAND: Wide

SMART BRAKE SYSTEM

DYNAMIC BRAKE

MAX BRAKE STRENGTH: 0 %

DYNAMIC CURVE:

TRIGGER RPM:

DRAG BRAKE: 0 %

MOTOR POWER

ACCELERATION BOOST

START RPM:

FINISH RPM:

MAX TIMING:

TOP SPEED TIMING

SLEW RATE:

MAX TIMING:

MISC

Battery Cut Off: 6.2V

SBEC: 6.0

RUN MODE: Practice

FIRMWARE: Latest



RESULT:

OBSERVATIONS

REMARKS: