

## Setup Sheet



Driver: Date:	_			
Event:			705	
Track:	-		TOE	-
Composition: Asphalt Carpet Other:	_			ĮĮ Į
Surface: Bumpy Both Smooth	-		(000)	
Layout: Open Mixed Tight				//_//
Traction: Low Medium High				<del>/   /</del> /
	•			<del></del> //// !
Front				
Toe: Caster:	•			
Carring:	-			
Spring:	•			
Track width:	-	1 15/1/17		74
Ride height:				
<del></del>			000	
<del></del>		\ \\		
		\@		
		T		
		1		
		//		
		//	9	
Front wing: Kit Other:				
Front tire:	_			
Front tire: Treatment:	_			
Surface & time:	_			
	-			
Rear				1 BATTERY
Damper oil:				POSITION
Damper spring:	-	<b>\  •</b>		/2 103111011
Damper spring preload:		V		
Side spring preioda:				
Side spring:Side spring preload:		0		
Damper tube:	-			
Rear chassis: Carbone Aluminum				
	•			
Track width:	-			
Ride height: -2mm -1mm 0 1mm 2mm				
<del></del>				
				₹
			0.1.0	
Rear wing: Kit Carbone Other:				
Rear wing position: Low Medium High	-			
Rear tire:			200	
Diameter: Treatment:	-			
Surface & time:	-	f		
			000	
Motor:	•			The last
Pinion / Spur: / Pitch: Rollout:	-			
ESC:	-			
ESC setting:				
Battery:				
Servo:	_			
Radio:	_			
Receiver:	-			
	CASTER			
Comments:	2° 4°			be d
	1 6° 8°			
	*/,*			
	A $A$			
			т	
	+			
(a)			CAS	STER
			#	
		~ ~		_
	n n			
	Щ ДД <sup>Т</sup>			
	~ d		~ // E	