

			TOE	
Driver: Date:		OUT		IN OUT
Event: Track:	_			_
Composition: Asphalt Carpet Other:				≥ >} ∦
Surface: Bumpy Both Smooth	_			
Layout: Open Mixed Tight Traction: Low Medium High	_		000	
Front	CASTER			
Spring:	-			[
Ride height:	_ (
1				
□2 mm □3 mm □4 mm				
Front tire: Treatment:				
Surface & time:	6°			
Center	1 19) 1			
Oil:				
Piston hole:	- (
Damper spring:	90			–1 □
Side Absorber lube:	<u> </u>	6		BATTERY
Side spring:	.	4		POSITION 2
Side spring preload:		7		/2 🗆
Rear	12°			
Track width:	- \(0))			
-3 MM2 MM1 MM. 0 MM. +1 MM. +2 MM. +3 MM.				
	ACKERMANN			
Rear wing position: 1-Low 2-High				
Rear wing: Rear tire:				
Treatment:		<u> </u>		——∦
Surface & time:	- (0)			
Motor: Pinion / Spur: / Pitch:	_			
Pinion / Spur: / Pitch: ESC:	-	L.		-1
ESC setting:	ABSORBER		FRONT CAMBER	
Battery:	- ADSONDER	+ ##=	TROMI CAMBER	
Servo: Radio:				
Receiver:	O-RING 1 2 3		Ø	
Comments:	O-RING			
			┎╕╽ ╒╸╵══╸ ╢╟╾╩╾╢╟╼═╾╌┥╎ <u>╒╬╸╏</u> ╫╴═┱┰┈╵╒╦╾╶┾╬╶╶╤╗╶┄╻╘═╶╫╴╢║	—
		WD	1	

