

NAME							
DATE							
TRACK							
TRACK CONDITION							
SURFACE [SMOOTH		ME	MEDIUM BUMPY		
SIZE		TIGHT		MEDIUM FAST			
TRACTION		LOW		MEI	DIUM	HIGH	
TRANSIN	IISS						
FRONT		SOLID AXLE OIL				OIL	
		DIFFER					
REAR							
PINION SPUR GEAR							
FINAL DR	IVE	RATIO					
SHOCKS							
SPRINGS:			COLOUR				
FRONT							
REAR OIL:							
- '							
PISTON:		m			+		
ANTI-ROLL BAR							
FRONT REAR			mm				
BODY			WING				
ROLL CEN	VTE	R	VVI	NG			
FRONT					mn	n	
REAR			mm				
ECCENTRIC BUSHINGS							
FRONT - FRONT							
	<u> </u>						
\bigcirc	_				_	0)	
	<u> </u>	1	_				
<u>(25</u> 2)□			0			(25 Z	
(3 1.5) <u></u>			0.5°			(3.1.5)	
REAR - FRONT							
	ر (\uparrow_{\square}		Г	<u>√</u>	// /_	
CTANDARD							
25 2 STANDARD (2 92) POSITION							
REAR - REAR							
MEAN - NEAN							
(0	1					′ 0)	
	_					ارسے	
3.5						3.5 1)	
					_	\simeq	
(a.r €) □						3 1.5	
<u>(25 2)</u> □			□ (2.5 2)				
<u>(25</u> 2)□			(2.5 2)				
3 1.5			☐ €.1 €				
(3.5 1)			3.5 1				
(3.5 1)							
REAR - FRONT							
)	}		_	\mathcal{K}		
	_	CTAN	/ID V D	_ L			
2.5	2		NDAR ITION		E	97	
_		. 03		•	_		

