

STX.8

Name: _____

Date: _____

Track: _____

Track Condition

Composition: ☐ Asphalt ☐ Carpet

Surface: ☐ Smooth ☐ Bumpy

Traction: ☐ Low ☐ Medium ☐ High

Size: ☐ Tight ☐ Medium ☐ Open

Track Temp.: _____ Air Temp.: _____

Electronics

Motor: _____ Timing: _____

ESC: _____ Battery: _____

Spur: _____ Pinion: _____ Final Ratio: _____

Aerodynamics

Body: _____ Wing: _____

Front Shocks Rear

- Spring - _____

- Oil - _____

- Piston - _____

- Length (mm) - _____

- Rebound (%) - _____

Anti-Roll Bar

Tires

- Inserts - _____

- Rims - _____

- Additive - _____

- Additive Time - _____



Upperdeck

☐ 1-Piece ☐ 2-Pieces

Transmission

- Oil - _____

- Oil Weight (Grs) - _____

- Setting - _____

☐ Solid Axle

Roll Center

- Setting - _____

Front-Front

(2.5 2) 0° (2 5'2)

(3 1.5) 0.5° (5'1 8)

☐ Alu ☐ Brass

Rear-Rear

(1 5'8) (3.5 1)

(5'1 8) (3 1.5)

(2 5'2) (2.5 2)

(2.5 2) (2 5'2)

(3 1.5) (5'1 8)

(3.5 1) (1 5'8)

☐ Alu ☐ Brass

Front-Rear & Rear-Front

(2.5 2) Standard Position (2 5'2)

FR: ☐ Alu ☐ Brass

RF: ☐ Alu ☐ Brass

