

Driver Marcos FJ Surface Asphalt (Indoor/Outdoor) Carpet Qual 10th Track Temperature 100  
 Date 9-30-2018 Traction Low Medium High Dry Wet Result 1 in the Am Air Temperature 96  
 Track Valkaria Country USA Best Lap 14.6 Humidity \_\_\_\_\_ Remark \_\_\_\_\_

Front		Rear		Optional		On-Power Control System						
C-Hub <input checked="" type="checkbox"/> M <input type="checkbox"/> H	Hex Offset <u>0 mm</u> <u>+1 mm</u>	Camber <u>-2</u> <u>-2.25</u>	Ride Height <u>5.6 mm</u> <u>5.8 mm</u>	DownStop <u>5 mm</u> <u>4 mm</u>	Sway Bar <u>1.2 mm</u> <u>1.1 mm</u>	Hex Offset _____ mm	Camber _____	Ride Height _____ mm	DownStop _____ mm	Sway Bar _____ mm	Steering Block <input type="checkbox"/> M <input type="checkbox"/> H	Suspension Arm <input type="checkbox"/> M <input type="checkbox"/> H

Front Toe Out <u>-1</u>	Lower Arm Spacer <u>0 mm</u>	Shock Tower Spacer <u>0 mm</u>	Bump Steer Spacer <u>.5 mm</u>	Weight _____ g	Spacer <u>4 mm</u>	<input checked="" type="checkbox"/> Floating Steering <input type="checkbox"/> Non-Floating Steering	Rear Toe In <u>-3</u>	Lower Arm Spacer <u>1 mm</u>	Shock Tower Spacer <u>0 mm</u>	Weight _____ g
-------------------------	------------------------------	--------------------------------	--------------------------------	----------------	--------------------	---------------------------------------------------------------------------------------------------------	-----------------------	------------------------------	--------------------------------	----------------

Suspension Mount Setup		Optional		Optional		Center Line Flex Control	
		<input type="checkbox"/> Turnbuckle <input type="checkbox"/> Carbon Fiber <input type="checkbox"/> None				<input type="checkbox"/> Center Post <input type="checkbox"/> Nut	
<input type="checkbox"/> 1 <input type="checkbox"/> 0.5	<input type="checkbox"/> 1 <input type="checkbox"/> 0.5	Spacer _____ mm	<input type="checkbox"/> 1 <input type="checkbox"/> 0.5	Lower Screw <input type="checkbox"/>			

Damper Setup		Transmission Setup		Servo		Tires	
Spring <u>RaceOpt 2.5</u>	Oil <u>35wt</u>	Rebound <u>0</u>	Piston <u>Peripheral</u>	Length <u>10.1mm</u>	Foam Insert <input type="checkbox"/>	Hole In Cap <input type="checkbox"/>	
Front <u>RaceOpt 2.5</u>	Rear <u>RaceOpt 2.5</u>	Oil <u>35wt</u>	Rebound <u>0</u>	Piston <u>Peripheral</u>	Length <u>10.1mm</u>	Foam Insert <input type="checkbox"/>	Hole In Cap <input type="checkbox"/>
Front <u>Spool</u>	Gear Diff _____	Oil _____	Weight _____ g	Position <u>Low High</u>			
Rear _____	Gear Diff _____	Oil <u>3k</u>	Weight <u>1.3 g</u>	Position <u>Low High</u>			
Servo <u>Savox</u>	Tires <u>Solaris36</u>	Esc <u>XR10</u>	Additive <u>RedDot</u>	Motor <u>TrinityMax</u>	Body <u>TypeS</u>	Spur <u>P/</u>	T Rear Wing <u>Stock</u>
Pinon <u>P/</u>	T FDR <u>3.96</u>						

Used Xray Peripheral shocks. Ran 1mm shorter wheelbase in the rear. No aluminum braces in the bulkheads. Tire warmers set 104 degrees for 15 minutes before the run.