XPRESS EXECUTE XQ10 SET-UP SHEET

Driver	Hay	Track Surface	Indoor	Carpet		Track Temperture	
Date	20-3-2021	Track Traction	Medium	Result		Air Temperature	
Track		Country	Hong Kong	Best Lap	10.7	Humidity	
Remark	0.75 Offset Rear Mounts, Soft Chassis						

Front

Spacer 1.5 mm

Spacer 2 mm

3 2 1

5.2 5.0 4.8 4.6 4.4 4.2 4

XPRESS

Rear

Spacer 1 mm

1 2 3

Spacer 2 mm

4 4.2 4.4 4.6 4.8 5.0 5.

	Front	Rear
Hex Offset	5 mm	4.5 mm
Camber	2 °	2 °
Ride Height	5 mm	5 mm
DownStop	5.4 mm	4.4 mm
Sway Bar	1.3 mm	1.2 mm

Camber Link

C-Hub ☐ M ☒ H

Steering Block ☐ M ☒ H

Suspension Arm ☐ M ☒ H

Rear Hub ☐ M ☒ H

Suspension Arm ☐ M ☒ H

Camber Link

Optional

On-Power Control System

Spacer mm

Spacer mm

Spacer mm

Spacer mm

Hex Offset mm

Camber °

Ride Height mm

DownStop mm

Sway Bar 1.2 mm

Steering Block ☐ M ☐ H

Suspension Arm ☐ M ☐ H

Front Toe Out 1.5 °

Front Tire Additive Area

Spacer 1 mm

Bump Steering Spacer 3 mm

Lower Arm Spacer 1 mm

1

2

Link Spacer 0.5 mm

Shock Tower Spacer 2 mm

Weight 10 g

Spacer 8 mm

Wheelbase Spacer

FF 1 mm

FR 1 mm

Rear Toe In 3 °

Rear Tire Additive Area

Lower Arm Spacer 1 mm

Shock Tower Spacer 2 mm

Link Spacer 0 mm

Wheelbase Spacer

RF 1 mm

RR 1 mm

Weight g

Suspension Mount Setup

FF

☐ 1 ☒ Aluminium

☒ 0.5 ☐ Brass

FR

☐ 1 ☒ Aluminium ☒ Spilt

☐ 0.5 ☐ Brass ☐ Solid

RR

☐ 1 ☒ Aluminium

☐ 0.5 ☐ Brass

RF

☐ 1 ☒ Aluminium ☒ Spilt

☐ 0.5 ☐ Brass ☐ Solid

Flex Control

☒ Graphite Chassis

☒ Aluminum Chassis

☐ Nut

☒ Center Post

Front Under Chassis Stiffener

☒ None

☐ Graphite

☐ Brass

☐ Standard Battery

☐ Short Battery (Forward Position)

☒ Short Battery (Backward Position)

Rear Under Chassis Stiffener

☒ None

☐ Graphite

☐ Brass

Damper Setup

	Front	Rear
Spring	Yokomo 2.4-2.9	Yokomo 2.45-2.75
Oil	450	450
Rebound	0	0
Piston	4	4
Length		
Foam Insert	☐	☐
Hole In Cap	☐	☐

Transmission Setup

	Front	Rear
	Spool	Gear Diff
Oil		5000
Weight	g	1.1 g
Position	High	High

Others

Servo

Tires Control

Esc Dash

Additive V3

Motor Dash 5.5T

Body Xtreme

Spur 64 P/ 110 T

Rear Wing STD

Pinon 64 P/ 31 T

FDR 6.741