XPRESS EXECUTE XQ10 SET-UP SHEET

Driver	Lolosam	Track Surface	Outdoor	Asphalt	Track Temperture		
Date	19/12/2021	Track Traction	Medium	Result	TQ+A1	Air Temperature	
Track	TRCC	Country		Best Lap	15.0	Humidity	Remark

Front

Spacer 1 mm

Spacer 3 mm

3 2 1

5.2 5.0 4.8 4.6 4.4 4.2 4

XPRESS

Rear

Spacer 3 mm

1 2 3

Spacer 1 mm

4 4.2 4.4 4.6 4.8 5.0 5.

	Front	Rear
Camber Link		Camber Link
C-Hub	☐ M ☒ H	
Steering Block	☐ M ☒ H	
Suspension Arm	☐ M ☒ H	
Hex Offset	4.25 mm	4.5 mm
Camber	1.5 °	1.5 °
Ride Height	5 mm	5.4 mm
DownStop	☐ 5.6 mm	5 mm
Sway Bar	1.3 mm	1.3 mm
Rear Hub		☐ M ☒ H
Suspension Arm		☐ M ☒ H

Optional — On-Power Control System

Spacer mm

Spacer mm

Spacer mm

Spacer mm

Hex Offset	mm
Camber	°
Ride Height	mm
DownStop	mm
Sway Bar	1.2 mm
Steering Block	☐ M ☐ H
Suspension Arm	☐ M ☐ H

Front Toe Out 1 °

Front Tire Additive Area

Spacer 0 mm

Bump Steering Spacer 1 mm

☒ 1 ☐ 2

Lower Arm Spacer 0 mm

Link Spacer 0 mm

Shock Tower Spacer 0 mm

Weight 0 g

Spacer 1 mm

Wheelbase Spacer

FF 0.5 mm

FR 0.5 mm

Rear Toe In °

Rear Tire Additive Area

Lower Arm Spacer 0 mm

Shock Tower Spacer 0 mm

Link Spacer 0 mm

Wheelbase Spacer

RF 1 mm

RR 1 mm

Weight g

Suspension Mount Setup

FF

☐ 1 ☒ Aluminium

☒ 0.5 ☐ Brass

FR

☐ 1 ☒ Aluminium ☒ Spilt

☒ 0.5 ☐ Brass ☐ Solid

RR

☐ 1 ☒ Aluminium

☒ 0.5 ☐ Brass

RF

☐ 1 ☒ Aluminium ☒ Spilt

☒ 0.5 ☐ Brass ☐ Solid

Flex Control

☐ Graphite Chassis

☐ Aluminum Chassis

☐ Nut

☒ Center Post

Front Under Chassis Stiffener

☒ None

☐ Graphite

☐ Brass

☒ Standard Battery

☐ Short Battery (Forward Position)

☐ Short Battery (Backward Position)

Rear Under Chassis Stiffener

☒ None

☐ Graphite

☐ Brass

Damper Setup

	Front	Rear
Spring	2.35-2.75	2.7
Oil	350	450
Rebound	0	0
Piston	4	4
Length		
Foam Insert	☐	☐
Hole In Cap	☒	☒

Transmission Setup

Front		Rear	
	Spool	Gear Diff	
Oil		Oil	6000
Weight	g	Weight	g
Position	Low	Position	Low

Others

Servo	sanwa	Tires	
Esc	orca oe1	Additive	
Motor	5.0t orca	Body	
Spur	P/ T	Rear Wing	
Pinon	P/ T	FDR	NaN