XPRESS EXECUTE XQ10 SET-UP SHEET

Driver: Masaya | Track Surface: Outdoor, Asphalt | Track Temperture:
Date: | Track Traction: Medium | Result: | Air Temperature:
Track: Beetops | Country: | Best Lap: | Humidity: | Remark:

Front

Spacer 1.0 mm
Spacer 1.0 mm

Rear

Spacer mm
Spacer mm

Camber Link
C-Hub: M [ ] H [•]
Steering Block: M [ ] H [•]
Suspension Arm: M [ ] H [•]

Hex Offset 4.25 mm
Camber 1.5 °
Ride Height mm
DownStop mm
Sway Bar 1.3 mm

mm °
mm
mm
1.3 mm

Rear Hub: M [ ] H [•]
Suspension Arm: M [ ] H [•]
Camber Link

Optional — On-Power Control System

Spacer 1.0 mm
Spacer 1.5 mm
Spacer 2.0 mm
Spacer 1.0 mm

Hex Offset 4.75 mm
Camber 2.0 °
Ride Height mm
DownStop mm
Sway Bar 1.3 mm

Steering Block: M [ ] H [•]
Suspension Arm: M [ ] H [•]

Front Toe Out 1 °
Front Tire Additive Area
Lower Arm Spacer mm
Shock Tower Spacer mm
Wheelbase Spacer
FF mm
FR mm

Spacer 1 mm
Bump Steering Spacer 1 mm
[•] 1
[ ] 2
Link Spacer 0 mm
Weight 10 g
Spacer 3.0 mm

Rear Toe In 2 °
Rear Tire Additive Area
Lower Arm Spacer mm
Shock Tower Spacer 0 mm
Link Spacer mm
Wheelbase Spacer
RF mm
RR mm
Weight g

Suspension Mount Setup

FF: 1 [ ] Aluminium [•] / 0.5 [ ] Brass
RR: 1 [ ] Aluminium [•] / 0.5 [•] Brass
FR: 1 [ ] Aluminium [•] Spilt / 0.5 [ ] Brass [ ] Solid
RF: 1 [•] Aluminium [•] Spilt / 0.5 [ ] Brass [ ] Solid

Flex Control

[•] Graphite Chassis
[•] Aluminum Chassis
[ ] Nut
[•] Center Post

Front Under Chassis Stiffener: [•] None / [ ] Graphite / [ ] Brass
[•] Standard Battery
[ ] Short Battery (Forward Position)
[ ] Short Battery (Backward Position)
Rear Under Chassis Stiffener: [ ] None / [ ] Graphite / [•] Brass

Damper Setup

	Front	Rear
Spring	Axon2.5-2.8	Axon2.7
Oil	Axon30wt	Axon30wt
Rebound	9.5	9.5
Piston	4	4
Length		
Foam Insert	[ ]	[ ]
Hole In Cap	[•]	[•]

Transmission Setup

	Front	Rear
	Spool	Gear Diff
Oil		Axon5000
Weight	g	1.5 g
Position	High	High

Others

Servo: KO GP2 | Tires: RUSH36S
Esc: HWG2 | Additive: MR33V3
Motor: HWG3R17.5 | Body: TWPS
Spur: 112 P/ 64 T | Rear Wing: TW
Pinon: 35 P/ 64 T | FDR: 1.9