

XRAY T2008

FRONT

CASTER

0°

2°

4°

6°

DIVE

ROLL-CENTER

SHIM

/mm

+0.75

0.00

-0.75

5

RIDE HEIGHT/mm

WHEELBASE/mm

259

REAR

ROLL-CENTER

SHIM

/mm

+0.75

0.00

-0.75

2

1

0

RIDE HEIGHT/mm

5.3

C-HUB

M

H

ALU

STEERING BLOCK

M

H

ALU

OFFSET

STANDARD

SHIM

1

/mm

UPPER SHOCK POSITION

QUICK ROLL CENTER POSITION

MEASURE UNDER ARM

DOWNSTOP/mm

6.5

5

REAR HUB

M

H

ALU

OFFSET

STANDARD

TOE/deg.

OUT

IN

1

SHIM UNDER SHOCK

SHIM

0

/mm

SHIM FRONT

SHIM

1.5

/mm

SHIM REAR

SHIM

1.5

/mm

FINAL TOE IN

3

OUTBOARD TOE

0

OUTBOARD + INBOARD TOE

ANTI ROLL-BAR

SHIM UNDER SHOCK

SHIM

0

/mm

SHIM FRONT/REAR

1.5 mm

NO shim

OTHER

0.5

INBOARD SHIMS ARE USED IN ADDITION TO TRACK-WIDTH SHIMS

FRONT

1.5

CAMBER/deg.

1.5

REAR

FRONT ARM

HARD (H)

EXTRA-HARD (XH)

REAR ARM

HARD (H)

EXTRA-HARD (XH)

BALANCE/g

TOP DECK MULTI-FLEX SETTING

US TOP DECK

EU TOP DECK

BALANCE/g

ECCENTER

STANDARD

DIFF. POSITION

UP

DOWN

BALANCE/g

ECCENTER

STANDARD

DIFF. POSITION

UP

DOWN

BALANCE/g

FRONT

CHASSIS MULTI-FLEX SETTING

CHASSIS

EU 5-cell

CENTRAL ALU STAND

FRONT ALU STANDS (US)

BRACE (EU)

REAR ALU STANDS (US)

REAR