

XRAY T2008

FRONT

CASTER

0°

2°

4°

6°

DIVE

ROLL-CENTER

SHIM

/mm

+0.75

0.00

-0.75

5

RIDE HEIGHT/mm

WHEELBASE/mm

0

1

1

REAR

SQUAT

ROLL-CENTER

SHIM

/mm

+0.75

0.00

-0.75

2

1

0

RIDE HEIGHT/mm

5.2

C-HUB

M

H

ALU

STEERING BLOCK

M

H

ALU

OFFSET

STANDARD

SHIM

/mm

UPPER SHOCK POSITION

5 4 3 2 1

QUICK ROLL CENTER POSITION

3+ 4+ 3 2 1

LONG

SHORT

SHIM

/mm

1

/mm

REAR HUB

M

H

ALU

OFFSET

STANDARD

FRONT

6.2

DOWNSTOP/mm

5.5

REAR

OUT

IN

SHIM UNDER SHOCK

SHIM 2mm/mm

SHIM FRONT

SHIM 1.75/mm

SHIM REAR

SHIM 1.5/mm

TOE / degr.

FINAL TOE IN

2.5

OUTBOARD TOE

0

ANTI ROLL-BAR

SHIM UNDER SHOCK

SHIM /mm

SHIM FRONT/REAR

1.5 mm

NO shim

OTHER

OUTBOARD + INBOARD TOE

SHIM /mm

2.25

1.9

1.5

1.5

0.75

0.4

0

INBOARD TOE

SHIM /mm

2.25

1.9

1.5

1.5

0.75

0.4

0

FRONT

2

CAMBER / degr.

2

REAR

FRONT ARM

HARD (H)

EXTRA-HARD (XH)

REAR ARM

HARD (H)

EXTRA-HARD (XH)

BALANCE / g

TOP DECK MULTI-FLEX SETTING

US TOP DECK

EU TOP DECK

BALANCE / g

10

ECCENTER_{mm}

STANDARD

1

DIFF. POSITION

UP

DOWN

BALANCE / g

ECCENTER_{mm}

STANDARD

1

DIFF. POSITION

UP

DOWN

BALANCE / g

10

FRONT

CHASSIS MULTI-FLEX SETTING

CHASSIS

EU 5 cell

REAR

CENTRAL ALU STAND

FRONT ALU STANDS (US)

REAR ALU STANDS (US)

BRACE (EU)