

XRAY T2008

FRONT

CASTER

0°

2°

4°

6°

DIVE

ROLL-CENTER

SHIM

/mm

+0.75

0.00

-0.75

WHEELBASE/mm

259

4.2

RIDE HEIGHT/mm

SQUAT

ROLL-CENTER

SHIM

/mm

+0.75

0.00

-0.75

RIDE HEIGHT/mm

4.4

C-HUB

M

H

ALU

STEERING BLOCK

M

H

ALU

OFFSET

STANDARD

+0.75

SHIM

0

/mm

UPPER SHOCK POSITION

5

4

3

2

1

LONG

SHORT

QUICK ROLL CENTER POSITION

3+

4+

3

4

1

2

SHIM

3

/mm

REAR HUB

M

H

ALU

OFFSET

STANDARD

+

MEASURE UNDER ARM

8

7

6

5

4

3

2

1

0

0

-1

-2

DOWNSTOP/mm

0

MEASURE UNDER ARM

10

9

8

7

6

5

4

3

2

1

0

0

-1

-2

FRONT

REAR

OUT

IN

SHIM UNDER SHOCK

SHIM

/mm

SHIM FRONT

SHIM

1.5

/mm

SHIM REAR

SHIM

1.25

/mm

TOE/deg.

FINAL TOE IN

3

OUTBOARD TOE

1.0

OUTBOARD + INBOARD TOE

ANTI ROLL-BAR

SHIM UNDER SHOCK

SHIM

/mm

SHIM FRONT/REAR

1.5 mm

NO shim

OTHER

2mm

INBOARD TOE

SHIM/mm

2.25

=3°

1.9

=2.5°

1.5

=2°

1.5

=1.5°

0.75

=1°

0.4

=0.5°

0

=0°

OUTER ACKERMANN POSITION

1

2

INNER ACKERMANN POSITION

1

2

SERVO SAVER

INBOARD SHIMS ARE USED IN ADDITION TO TRACK-WIDTH SHIMS

FRONT

REAR

FRONT

1.5

CAMBER/deg.

2

REAR

FRONT ARM

HARD (H)

EXTRA-HARD (XH)

REAR ARM

HARD (H)

EXTRA-HARD (XH)

BALANCE/g

TOP DECK MULTI-FLEX SETTING

US TOP DECK

EU TOP DECK

BALANCE/g

ECCENTER

STANDARD

DIFF. POSITION

UP

DOWN

ECCENTER

STANDARD

DIFF. POSITION

UP

DOWN

BALANCE/g

BALANCE/g

FRONT

REAR

FRONT

CHASSIS MULTI-FLEX SETTING

CHASSIS

CENTRAL ALU STAND

FRONT ALU STANDS (US)

REAR ALU STANDS (US)

BRACE (EU)