

XRAY T2008

FRONT

CASTER

0°

2°

4°

6°

DIVE

ROLL-CENTER

SHIM

/mm

+0.75

0.00

-0.75

5

RIDE HEIGHT/mm

WHEELBASE/mm

0

1

1

REAR

SQUAT

ROLL-CENTER

SHIM

/mm

+0.75

0.00

-0.75

2

1

0

RIDE HEIGHT/mm

5,5

C-HUB

M

H

ALU

STEERING BLOCK

M

H

ALU

OFFSET

STANDARD

-0,75

SHIM

1

/mm

UPPER SHOCK POSITION

5 4 3 2 1

LONG

SHORT

QUICK ROLL CENTER POSITION

0 1 2 3 4

MEASURE UNDER ARM

8 7 6 5 4 3 2 1 0 -1 -2

DOWNSTOP/mm

6

SHIM

2

/mm

UPPER SHOCK POSITION

1 2 3 4 5 6

LONG

SHORT

MEASURE UNDER ARM

-2 -1 0 1 2 3 4 5 6 7 8 9 10

DOWNSTOP/mm

5

REAR HUB

M

H

ALU

OFFSET

STANDARD

+0,75

FRONT

6

DOWNSTOP/mm

5

REAR

OUT

0,5

SHIM UNDER SHOCK

SHIM

1

/mm

SHIM FRONT

SHIM

1,5

/mm

SHIM REAR

SHIM

1,5

/mm

TOE/deg.

FINAL TOE IN

3

OUTBOARD TOE

0.0

OUTBOARD + INBOARD TOE

ANTI ROLL-BAR

SHIM UNDER SHOCK

SHIM

0

/mm

SHIM FRONT/REAR

1.5 mm

NO shim

OTHER

INBOARD TOE

SHIM/mm

2,5

-3°

1,9

-2,5°

1,5

-2°

1,15

-1,5°

0,75

-1°

0,4

-0,5°

0

-0°

FRONT

1

CAMBER/deg.

2

REAR

FRONT ARM

HARD (H)

EXTRA-HARD (XH)

REAR ARM

HARD (H)

EXTRA-HARD (XH)

BALANCE/g

ECCEMTER_{mm}

STANDARD

1

DIFF. POSITION

UP

DOWN

BALANCE/g

TOP DECK MULTI-FLEX SETTING

US TOP DECK

EU TOP DECK

BALANCE/g

ECCEMTER_{mm}

STANDARD

1

DIFF. POSITION

UP

DOWN

BALANCE/g

FRONT

CHASSIS MULTI-FLEX SETTING

REAR

CHASSIS

CENTRAL ALU STAND

FRONT ALU STANDS (US)

REAR ALU STANDS (US)

BRACE (EU)