

XRAY T2008

FRONT

CASTER
☐ 0° ☐ 2° ☒ 4° ☐ 6°

SQUAT **ROLL-CENTER**

DIVE **ROLL-CENTER**
☒ +0.75 ☐ 0.00 ☐ -0.75

SHIM
☒ +0.75 ☐ 0.00 ☐ -0.75

WHEELBASE /mm
☒ 5

WHEELBASE /mm
☒ 2 ☐ 1 ☐ 0

5 **RIDE HEIGHT** /mm

RIDE HEIGHT /mm **5**

REAR

SHIM
☐ /mm

SHIM
☐ /mm

REAR HUB
☐ M ☐ H ☐ ALU

OFFSET
☒ STANDARD

3 **DOWNSTOP** /mm

4 **DOWNSTOP** /mm

FRONT

OUT ☐ **IN** ☒ 0

SHIM UNDER SHOCK
SHIM /mm

SHIM FRONT
SHIM 1.5 /mm

SHIM REAR
SHIM 0.75 /mm

TOE /deg.
FINAL TOE IN 3 **OUTBOARD TOE** 0

ANTI ROLL-BAR
SHIM UNDER SHOCK
SHIM /mm

SHIM FRONT/REAR
☐ 1.5 mm ☒ NO shim ☐ OTHER

INBOARD TOE
SHIM /mm
☒ 2.5° ☐ 2° ☐ 1.5° ☐ 1° ☐ 0.5° ☐ 0°

REAR

FRONT ARM
☒ HARD (H) ☐ EXTRA-HARD (XH)

REAR ARM
☒ HARD (H) ☐ EXTRA-HARD (XH)

FRONT

BALANCE /g
15

TOP DECK MULTI-FLEX SETTING
US TOP DECK

ECCENTER mm
☒ STANDARD ☐ 1

DIFF. POSITION
☒ UP ☐ DOWN

BALANCE /g

EU TOP DECK

REAR

BALANCE /g
20

TOP DECK MULTI-FLEX SETTING
US TOP DECK

ECCENTER mm
☒ STANDARD ☐ 1

DIFF. POSITION
☒ UP ☐ DOWN

BALANCE /g

EU TOP DECK

FRONT

CHASSIS MULTI-FLEX SETTING
CHASSIS 5 cells

CENTRAL ALU STAND

FRONT ALU STANDS (US)
☐ BRACE (EU)

REAR ALU STANDS (US)

REAR