

SET-UP SHEET

RX8E'23 SET-UP SHEET VER. 1 ©XRAY

XRAY RX8E'23

RACE		
TRACK		
NAME		DATE

QUAL POSITION	FINAL POSITION	BEST LAP TIME	LAPS	TIME
		/sec	/	

TRACKS			
TRACK CONDITION	☐ SMOOTH	☐ MEDIUM	☐ BUMPY
	☐ TECHNICAL	☐ MIXED	☐ FAST
TRACK TRACTION	☐ LOW	☐ MEDIUM	☐ HIGH

GEARING			
PINION	22 ☐	23 ☐	24 ☐
	25 ☐		
SPUR	53 ☐	54 ☐	55 ☐
	57 ☐	58 ☐	59 ☐
	60 ☐		
RATIO			

FRONT	SHOCKS	REAR
	SPRING	
	OIL	
	REBOUND	
☐ YES ☐ NO	FOAM INSERTS	☐ YES ☐ NO
	PISTONS	
☐ 2 HOLES	☐ 1.0mm	☐ 2 HOLES
☐ 3 HOLES	☐ 1.1mm	☐ 3 HOLES
☐ OTHER	☐ 1.2mm	☐ OTHER

FRONT	WIRE	REAR

FRONT	TIRES	REAR
LEFT	RIGHT	
	MANUFACTURER	
	SHORE /degr.	
mm	mm	mm
mm	5 MIN. WEAR	mm
	RUBBER TIRES	

ELECTRONICS	
MOTOR	
SPEEDO	
BATTERY TYPE	

BODY	
------	--

WING	HEIGHT
------	--------

COMMENTS

FRONT

AERO DISK

YES ☐ NO ☐

ECCENTER

BUMP STEER SHIM

mm

FRONT

WHEELBASE

0mm 2mm /mm

FRONT

RIDE HEIGHT

mm

WHEEL DIAMETER

mm

REAR

WHEELBASE

2mm 0mm

REAR

RIDE HEIGHT

mm

WHEEL DIAMETER

mm

STEER. BLOCK

MEDIUM ☐

HARD ☐

GRAPHITE ☐

UPPER ARM

MEDIUM ☐

HARD ☐

GRAPHITE ☐

ROLL CENTER

SHOCK SHIM

mm

SHIM

mm

UPPER SHOCK POSITION

1 2 3

ROLL CENTER

UPPER ARM

MEDIUM ☐

HARD ☐

GRAPHITE ☐

SHIM

mm

LOWER ARM

G H M M H G

#107701 SUPPORT BLOCKS

HUDY

MEASURE UNDER STEERING BLOCK

mm

FRONT DOWNSTOP

mm

REAR DOWNSTOP

mm

MEASURE UNDER REAR UPRIGHT

mm

FRONT

TOE OUT

OUTER ACKERMANN POSITION

1 2 3

UPPER ARM SHIMS

0 1 2 3 4

FRONT BRACE

YES ☐ NO ☐

SERVO SAVER

4 3 2 1

FRONT BRACE

YES ☐ NO ☐

FLEX SCREW

YES ☐ NO ☐

REAR

TOE IN

FRONT

CAMBER/degr.

LEFT

RIGHT

SHOCK PLATE

STEEL ☐

GRAPHITE ☐

LONG ☐

SHORT ☐

SUSP. HOLDERS

STANDARD ☐

+2mm ☐

ROLL CENTER

SHIM

mm

CAMBER/degr.

LEFT

RIGHT

CAMBER LINK LOCATION

1 2

FRONT

TRACK WIDTH

mm

REAR

TRACK WIDTH

mm

FRONT

BUMPER WINDOW

CUT ☐ NO-CUT ☐

FRONT BALANCE

GRAPHITE ☐

ALU ☐

FRONT BRACE

YES ☐ NO ☐

BALANCE/g

REAR

BODY 1 MOUNT

2