

XRAY T2'007

FRONT

CASTER
☐ 0° ☐ 2° ☒ 4° ☐ 6°

DIVE ROLL-CENTER
☐ +0.75
☒ 0.00
☐ -0.75

SHIM
☐ +0.75
☒ 0.00
☐ -0.75

WHEELBASE/mm

5

255

2 2 1

RIDE HEIGHT/mm

5

255

2 2 1

RIDE HEIGHT/mm

5

255

2 2 1

SQUAT ROLL-CENTER REAR

CASTER
☐ 0° ☐ 2° ☒ 4° ☐ 6°

DIVE ROLL-CENTER
☐ +0.75
☒ 0.00
☐ -0.75

SHIM
☐ +0.75
☒ 0.00
☐ -0.75

WHEELBASE/mm

5

255

2 2 1

RIDE HEIGHT/mm

5

255

2 2 1

RIDE HEIGHT/mm

5

255

2 2 1

FRONT

C-HUB
☒ STANDARD
☐ ALU

SHIM
☐ 0 /mm

UPPER SHOCK POSITION

5 4 3 2 1

1 2 3 4 5 6

STEERING BLOCK
☒ PLASTIC
☐ ALU

SHIM
☐ 1 /mm

QUICK ROLL CENTER POSITION

2 1

1 2

OFFSET
☐ STANDARD

REAR HUB
☒ PLASTIC
☐ ALU

LOWER SHOCK POSITION

8 7 6 5 4 3 2 1 0 -1 -2 -3

0

2 -1 0 1 2 3 4

MEASURE UNDER ARM

8 7 6 5 4 3 2 1 0 -1 -2 -3

0

2 -1 0 1 2 3 4

MEASURE UNDER ARM

8 7 6 5 4 3 2 1 0 -1 -2 -3

0

2 -1 0 1 2 3 4

FRONT

6mm

DOWNSTOP /mm

4mm

REAR

6mm

DOWNSTOP /mm

4mm

TOE / deg.

OUT IN
☐ 1

FINAL TOE IN
☐ 3

OUTBOARD TOE
☐ 1.0

OUTBOARD + INBOARD TOE

1 2 3 4 5

1 2 3 4 5 6

SHIM FRONT
☐ 1.5 /mm

SHIM REAR
☐ 1.5 /mm

ACKERMANN POSITION

1 2

1 2

SHIM FRONT/REAR
☒ 1.5 mm
☐ NO shim
☐ OTHER

INBOARD TOE SHIM /mm
☒ 1.5 = 2°
☐ 1.5 = 1.5°
☐ 0.75 = 1°
☐ 0.4 = 0.5°
☐ 0 = 0°

FRONT

OUT IN
☐ 1

FINAL TOE IN
☐ 3

OUTBOARD TOE
☐ 1.0

OUTBOARD + INBOARD TOE

1 2 3 4 5

1 2 3 4 5 6

SHIM FRONT
☐ 1.5 /mm

SHIM REAR
☐ 1.5 /mm

ACKERMANN POSITION

1 2

1 2

SHIM FRONT/REAR
☒ 1.5 mm
☐ NO shim
☐ OTHER

INBOARD TOE SHIM /mm
☒ 1.5 = 2°
☐ 1.5 = 1.5°
☐ 0.75 = 1°
☐ 0.4 = 0.5°
☐ 0 = 0°

TOE / deg.

OUT IN
☐ 1

FINAL TOE IN
☐ 3

OUTBOARD TOE
☐ 1.0

OUTBOARD + INBOARD TOE

1 2 3 4 5

1 2 3 4 5 6

SHIM FRONT
☐ 1.5 /mm

SHIM REAR
☐ 1.5 /mm

ACKERMANN POSITION

1 2

1 2

SHIM FRONT/REAR
☒ 1.5 mm
☐ NO shim
☐ OTHER

INBOARD TOE SHIM /mm
☒ 1.5 = 2°
☐ 1.5 = 1.5°
☐ 0.75 = 1°
☐ 0.4 = 0.5°
☐ 0 = 0°

FRONT

OUT IN
☐ 1

FINAL TOE IN
☐ 3

OUTBOARD TOE
☐ 1.0

OUTBOARD + INBOARD TOE

1 2 3 4 5

1 2 3 4 5 6

SHIM FRONT
☐ 1.5 /mm

SHIM REAR
☐ 1.5 /mm

ACKERMANN POSITION

1 2

1 2

SHIM FRONT/REAR
☒ 1.5 mm
☐ NO shim
☐ OTHER

INBOARD TOE SHIM /mm
☒ 1.5 = 2°
☐ 1.5 = 1.5°
☐ 0.75 = 1°
☐ 0.4 = 0.5°
☐ 0 = 0°

TOE / deg.

OUT IN
☐ 1

FINAL TOE IN
☐ 3

OUTBOARD TOE
☐ 1.0

OUTBOARD + INBOARD TOE