

XRAY T2'007

FRONT

CASTER
☐ 0° ☐ 2° ☒ 4° ☐ 6°

DIVE ROLL-CENTER
☐ +0.75
☒ 0.00
☐ -0.75

SHIM
☐ +0.75
☒ 0.00
☐ -0.75

WHEELBASE /mm

5 **RIDE HEIGHT** /mm

SQUAT ROLL-CENTER

☐ +0.75
☒ 0.00
☐ -0.75

☐ +0.75
☒ 0.00
☐ -0.75

2 **2** **1**

5 **RIDE HEIGHT** /mm

FRONT

C-HUB
☒ STANDARD
☐ ALU

SHIM
 1 /mm

STEERING BLOCK
☒ PLASTIC
☐ ALU

UPPER SHOCK POSITION
 5 4 3 2 1

SHIM
 2 /mm

OFFSET
☐ STANDARD

QUICK ROLL CENTER POSITION
 1 2

REAR HUB
☒ PLASTIC
☐ ALU

MEASURE UNDER ARM
 8 7 6 5 4 3 2 1 0 1 2 3 4

5.5 **DOWNSTOP** /mm

5

REAR

LOWER SHOCK POSITION
 1 2

MEASURE UNDER ARM
 2 1 0 1 2 3 4 5 6 7 8 9 10

FRONT

OUT .5 **IN**

TOE / deg.

FINAL TOE IN 2.5 **OUTBOARD TOE** 1.0

SHIM FRONT
 1.15 /mm

SHIM REAR
 /mm

REAR

SHIM FRONT/REAR
☐ 1.5 mm
☐ NO shim
☐ OTHER

INBOARD TOE
 SHIM /mm
 1.5 = 2°
 1.5 = 1.5°
 0.5 = 1°
 0.4 = 0.5°
 0 = 0°

FRONT

1.5

CAMBER / deg.

1.5

FRONT ARM
☒ HARD (H)
☐ EXTRA-HARD (XH)

REAR ARM
☒ HARD (H)
☐ EXTRA-HARD (XH)

REAR

28

14

FRONT

BALANCE /g

TOP DECK MULTI-FLEX SETTING

BALANCE /g

28

14

REAR

28

14

FRONT

CHASSIS MULTI-FLEX SETTING

FRONT ALU STAND

REAR

REAR ALU STAND