

XRAY T2008

FRONT

CASTER
☐ 0° ☐ 2° ☒ 4° ☐ 6°

SQUAT **ROLL-CENTER**

DIVE **ROLL-CENTER**
☐ +0.75 ☒ 0.00 ☐ -0.75

SHIM
☐ +0.75 ☒ 0.00 ☐ -0.75

☐ 0 ☒ 1 ☐ 1

WHEELBASE /mm

☒ 2 ☐ 1 ☐ 0

5.4 **RIDE HEIGHT** /mm

RIDE HEIGHT /mm **5.4**

REAR

C-HUB
☒ M ☐ H ☐ ALU

SHIM
☐ 1 /mm

STEERING BLOCK
☒ M ☐ H ☐ ALU

UPPER SHOCK POSITION
☒ LONG ☐ SHORT

QUICK ROLL CENTER POSITION
☒ LONG ☐ SHORT

SHIM
☐ 1 /mm

MEASURE UNDER ARM
 8 7 6 5 4 3 2 1 0 -1 -2

0 1/2 **HUDY**

MEASURE UNDER ARM
 -2 -1 0 1 2 3 4 5 6 7 8 9 10

6 **DOWNSTOP** /mm

5

FRONT

OUT ☐ **IN** ☒ **.5**

TOE /deg.
FINAL TOE IN ☐ **3** **OUTBOARD TOE** ☐ **1.0**

SHIM UNDER SHOCK
SHIM /mm

OUTER ACKERMANN POSITION
☐ 1 ☐ 2

SHIM FRONT
SHIM **1.5** /mm

INNER ACKERMANN POSITION
☐ 1 ☐ 2

SHIM REAR
SHIM **1.5** /mm

SERVO SAVER

REAR

ANTI ROLL-BAR
SHIM UNDER SHOCK
SHIM /mm

SHIM FRONT/REAR
☐ 1.5 mm ☒ NO shim ☐ OTHER

SHIM /mm
☐ 2.5 ☐ 2.0 ☒ 1.5 ☐ 1.0 ☐ 0.5 ☐ 0

INBOARD TOE
☐ 3° ☐ 2.5° ☒ 2° ☐ 1.5° ☐ 1° ☐ 0.5° ☐ 0°

FRONT

1.25 **CAMBER** /deg.

1.5

FRONT ARM
☒ HARD (H) ☐ EXTRA-HARD (XH)

REAR ARM
☒ HARD (H) ☐ EXTRA-HARD (XH)

REAR

1.25 **CAMBER** /deg.

1.5

FRONT ARM
☒ HARD (H) ☐ EXTRA-HARD (XH)

REAR ARM
☒ HARD (H) ☐ EXTRA-HARD (XH)

FRONT

BALANCE /g
5

TOP DECK MULTI-FLEX SETTING
US TOP DECK

ECCENTER mm
☒ STANDARD ☐ 1

DIFF. POSITION
☒ UP ☐ DOWN

BALANCE /g
5

EU TOP DECK

REAR

BALANCE /g
10

TOP DECK MULTI-FLEX SETTING
US TOP DECK

ECCENTER mm
☒ STANDARD ☐ 1

DIFF. POSITION
☒ UP ☐ DOWN

BALANCE /g
10

EU TOP DECK

FRONT

CHASSIS MULTI-FLEX SETTING
CHASSIS

CENTRAL ALU STAND

FRONT ALU STANDS (US)
☐ BRACE (EU)

REAR ALU STANDS (US)

REAR

CHASSIS MULTI-FLEX SETTING
CHASSIS

CENTRAL ALU STAND

FRONT ALU STANDS (US)
☐ BRACE (EU)

REAR ALU STANDS (US)