

XRAY T2008

FRONT

CASTER

0°

2°

4°

6°

DIVE

ROLL-CENTER

SHIM

1

/mm

+0.75

0.00

-0.75

WHEELBASE/mm

258

5.3

RIDE HEIGHT/mm

SQUAT

ROLL-CENTER

SHIM

1

/mm

+0.75

0.00

-0.75

RIDE HEIGHT/mm

5.8

C-HUB

M

H

ALU

STEERING BLOCK

M

H

ALU

OFFSET

STANDARD

SHIM

1

/mm

UPPER SHOCK POSITION

5 4 3 2 1

QUICK ROLL CENTER POSITION

3 2 1

SHIM

1.5

/mm

REAR HUB

M

H

ALU

OFFSET

STANDARD

FRONT

6.2

DOWNSTOP /mm

5.2

REAR

OUT

1

IN

SHIM UNDER SHOCK

SHIM

1.5

/mm

SHIM FRONT

SHIM

1.2

/mm

SHIM REAR

SHIM

1.2

/mm

TOE /deg.

FINAL TOE IN

2.5

OUTBOARD TOE

0.0

OUTBOARD + INBOARD TOE

ANTI ROLL-BAR

SHIM UNDER SHOCK

SHIM

0

/mm

SHIM FRONT/REAR

1.5 mm

NO shim

OTHER

INBOARD TOE

SHIM /mm

2.25

=3°

1.75

=2.5°

1.5

=2°

1.25

=1.5°

0.75

=1°

0.4

=0.5°

0

=0°

FRONT

2

CAMBER /deg.

2.5

REAR

FRONT ARM

HARD (H)

EXTRA-HARD (XH)

REAR ARM

HARD (H)

EXTRA-HARD (XH)

BALANCE /g

ECCENTER

STANDARD

DIFF. POSITION

UP

DOWN

BALANCE /g

TOP DECK MULTI-FLEX SETTING

US TOP DECK

EU TOP DECK

BALANCE /g

ECCENTER

STANDARD

DIFF. POSITION

UP

DOWN

BALANCE /g

FRONT

CHASSIS MULTI-FLEX SETTING

CHASSIS

EU 5-cell

CENTRAL ALU STAND

FRONT ALU STANDS (US)

BRACE (EU)

REAR ALU STANDS (US)

REAR