

XRAY T2008

FRONT

CASTER

0°

2°

4°

6°

DIVE

ROLL-CENTER

SHIM

/mm

+0.75

0.00

-0.75

WHEELBASE/mm

259

4.5

RIDE HEIGHT/mm

SQUAT

ROLL-CENTER

SHIM

/mm

+0.75

0.00

-0.75

WHEELBASE/mm

259

4.8

RIDE HEIGHT/mm

C-HUB

M

H

ALU

STEERING BLOCK

M

H

ALU

OFFSET

STANDARD

SHIM

1

/mm

UPPER SHOCK POSITION

5 4 3 2 1

QUICK ROLL CENTER POSITION

3+ 4+ 3 2 1

SHIM

1

/mm

REAR HUB

M

H

ALU

OFFSET

STANDARD

FRONT

6.5

DOWNSTOP /mm

5

REAR

OUT

1

SHIM UNDER SHOCK

SHIM

0

/mm

SHIM FRONT

SHIM

1.5

/mm

SHIM REAR

SHIM

1.5

/mm

TOE /deg.

FINAL TOE IN

3

OUTBOARD TOE

0.0

OUTBOARD + INBOARD TOE

ANTI ROLL-BAR

SHIM UNDER SHOCK

SHIM

0

/mm

SHIM FRONT/REAR

1.5 mm

NO shim

OTHER

0.5

INBOARD TOE

SHIM /mm

2.5

= 3°

1.9

= 2.5°

1.5

= 2°

1.15

= 1.5°

0.75

= 1°

0.4

= 0.5°

0

= 0°

FRONT

1.5

CAMBER /deg.

1.5

REAR

FRONT ARM

HARD (H)

EXTRA-HARD (XH)

REAR ARM

HARD (H)

EXTRA-HARD (XH)

BALANCE /g

ECCENTER

STANDARD

DIFF. POSITION

UP

DOWN

BALANCE /g

TOP DECK MULTI-FLEX SETTING

US TOP DECK

EU TOP DECK

BALANCE /g

ECCENTER

STANDARD

DIFF. POSITION

UP

DOWN

BALANCE /g

FRONT

CHASSIS MULTI-FLEX SETTING

CHASSIS

CENTRAL ALU STAND

FRONT ALU STANDS (US)

REAR ALU STANDS (US)

BRACE (EU)

REAR