

XRAY T2008

FRONT

CASTER

0°

2°

4°

6°

DIVE

ROLL-CENTER

SHIM

1

/mm

+0.75

0.00

-0.75

WHEELBASE/mm

0

1

1

5.2

RIDE HEIGHT/mm

SQUAT

ROLL-CENTER

+0.75

0.00

-0.75

WHEELBASE/mm

2

1

0

5.4

RIDE HEIGHT/mm

C-HUB

M

H

ALU

STEERING BLOCK

M

H

ALU

OFFSET

STANDARD

SHIM

1.5

/mm

UPPER SHOCK POSITION

5 4 3 2 1

QUICK ROLL CENTER POSITION

3 2 1

LONG

SHORT

SHIM

1.5

/mm

REAR HUB

M

H

ALU

OFFSET

STANDARD

FRONT

5.2

DOWNSTOP /mm

4.2

REAR

OUT

0.5

IN

SHIM UNDER SHOCK

SHIM

1.5

/mm

SHIM FRONT

SHIM

1.15

/mm

SHIM REAR

SHIM

1.15

/mm

TOE /deg.

FINAL TOE IN

3

OUTBOARD TOE

0

OUTBOARD + INBOARD TOE

ANTI ROLL-BAR

SHIM UNDER SHOCK

SHIM

/mm

SHIM FRONT/REAR

1.5 mm

NO shim

OTHER

INBOARD TOE

SHIM /mm

2.5

= 3°

1.9

= 2.5°

1.5

= 2°

1.15

= 1.5°

0.75

= 1°

0.4

= 0.5°

0

= 0°

FRONT

2

CAMBER /deg.

2

REAR

FRONT ARM

HARD (H)

EXTRA-HARD (XH)

REAR ARM

HARD (H)

EXTRA-HARD (XH)

BALANCE /g

TOP DECK MULTI-FLEX SETTING

US TOP DECK

EU TOP DECK

ECCENTER

STANDARD

DIFF. POSITION

UP

DOWN

BALANCE /g

BALANCE /g

CHASSIS MULTI-FLEX SETTING

CHASSIS

EU 5 cell

CENTRAL ALU STAND

FRONT ALU STANDS (US)

BRACE (EU)

REAR ALU STANDS (US)

ECCENTER

STANDARD

DIFF. POSITION

UP

DOWN

BALANCE /g

FRONT

REAR