

XRAY T2008

FRONT

CASTER
0° ☐ 2° ☐ 4° ☒ 6° ☐

SHIM
2 /mm

DIVE
+0.75 ☐ 0.00 ☒ -0.75 ☐

ROLL-CENTER
+0.75 ☐ 0.00 ☒ -0.75 ☐

WHEELBASE/mm
0 1 1

WHEELBASE/mm
2 1 0

5.2 **RIDE HEIGHT**/mm

5.4 **RIDE HEIGHT**/mm

REAR

SHIM
2 /mm

SHIM
2 /mm

UPPER SHOCK POSITION
5 4 3 2 1

QUICK ROLL CENTER POSITION
3+ 4+ 3 2 1

CAMBER LINK LOCATION
1 2

LONG ☒ **SHORT** ☐

LONG ☒ **SHORT** ☐

MEASURE UNDER ARM
8 7 6 5 4 3 2 1 0 -1 -2

MEASURE UNDER ARM
-2 -1 0 1 2 3 4 5 6 7 8 9 10

6 **DOWNSTOP** /mm

5 **DOWNSTOP** /mm

FRONT

OUT 0.5 **IN**

TOE /deg.
FINAL TOE IN 3 **OUTBOARD TOE** 0

SHIM UNDER SHOCK
SHIM 0 /mm

SHIM FRONT
SHIM 1.5 /mm

SHIM REAR
SHIM 1.5 /mm

OUTER ACKERMANN POSITION
1 2

INNER ACKERMANN POSITION
1 2

SERVO SAVER

REAR

ANTI ROLL-BAR
SHIM 0 /mm

SHIM UNDER SHOCK
SHIM 0 /mm

SHIM FRONT/REAR
1.5 mm ☐ NO shim ☒ OTHER

SHIM /mm
2.5 ☒ = 3°
1.9 ☐ = 2.5°
1.5 ☐ = 2°
1.15 ☐ = 1.5°
0.75 ☐ = 1°
0.4 ☐ = 0.5°
0 ☐ = 0°

FRONT

-1.5 **CAMBER** /deg.

-1.5 **CAMBER** /deg.

FRONT ARM
HARD (H) ☒ EXTRA-HARD (XH) ☐

REAR ARM
HARD (H) ☒ EXTRA-HARD (XH) ☐

REAR

BALANCE /g

BALANCE /g

TOP DECK MULTI-FLEX SETTING
US TOP DECK

EU TOP DECK

ECCENTER
STANDARD ☒ 1 ☐

DIFF. POSITION
UP ☒ DOWN ☐

BALANCE /g

BALANCE /g

FRONT

CHASSIS MULTI-FLEX SETTING
CHASSIS

CENTRAL ALU STAND

FRONT ALU STANDS (US)
BRACE (EU) ☐

REAR ALU STANDS (US)

REAR

BALANCE /g

BALANCE /g