

XRAY T2008

FRONT

CASTER

0°

2°

4°

6°

DIVE

ROLL-CENTER

SHIM

0

/mm

+0.75

0.00

-0.75

+0.75

0.00

-0.75

WHEELBASE/mm

0

1

1

5.8

RIDE HEIGHT/mm

SQUAT

ROLL-CENTER

+0.75

0.00

-0.75

+0.75

0.00

-0.75

2

1

0

6

RIDE HEIGHT/mm

REAR

C-HUB

M

H

ALU

SHIM

1.5

/mm

UPPER SHOCK POSITION

5

4

3

2

1

LONG

SHORT

QUICK ROLL CENTER POSITION

3+

3

4+

4

2

1

LONG

SHORT

SHIM

1.5

/mm

REAR HUB

M

H

ALU

STEERING BLOCK

M

H

ALU

OFFSET

STANDARD

MEASURE UNDER ARM

8

7

6

5

4

3

2

1

0

1

2

3

4

5

6

7

8

5

DOWNSTOP/mm

4

DOWNSTOP/mm

FRONT

REAR

OUT

IN

.5

SHIM UNDER SHOCK

SHIM

1.5

/mm

SHIM FRONT

SHIM

1.5

/mm

SHIM REAR

SHIM

1.5

/mm

OUTER ACKERMANN POSITION

1

2

3

4

5

INNER ACKERMANN POSITION

1

2

SERVO SAVER

TOE / degr.

FINAL TOE IN

3

OUTBOARD TOE

0

OUTBOARD + INBOARD TOE

ANTI ROLL-BAR

SHIM UNDER SHOCK

SHIM

0

/mm

SHIM FRONT/REAR

1.5 mm

NO shim

OTHER

INBOARD TOE

SHIM / mm

2.5

=3°

1.9

=2.5°

1.5

=2°

1.15

=1.5°

0.75

=1°

0.4

=0.5°

0

=0°

INBOARD SHIMS ARE USED IN ADDITION TO TRACK-WIDTH SHIMS

FRONT

1.5

CAMBER / degr.

1.5

REAR

FRONT ARM

HARD (H)

EXTRA-HARD (XH)

REAR ARM

HARD (H)

EXTRA-HARD (XH)

BALANCE / g

TOP DECK MULTI-FLEX SETTING

US TOP DECK

EU TOP DECK

BALANCE / g

ECCENTER_{mm}

STANDARD

DIFF. POSITION

UP

DOWN

FRONT

CHASSIS MULTI-FLEX SETTING

CHASSIS

CENTRAL ALU STAND

FRONT ALU STANDS (US)

REAR ALU STANDS (US)

BRACE (EU)

REAR