

XRAY T2008

FRONT

CASTER
☐ 0° ☐ 2° ☒ 4° ☐ 6°

SQUAT **ROLL-CENTER**

DIVE **ROLL-CENTER**
☐ +0.75 ☒ 0.00 ☐ -0.75

SHIM
☐ +0.75 ☒ 0.00 ☐ -0.75

☐ 0 ☒ 1 ☐ 1

WHEELBASE /mm

☒ 2 ☐ 1 ☐ 0

5 **RIDE HEIGHT** /mm

RIDE HEIGHT /mm **5,2**

REAR

C-HUB
☒ M ☐ H ☐ ALU

SHIM
☐ 1 /mm

STEERING BLOCK
☒ M ☐ H ☐ ALU

UPPER SHOCK POSITION
☒ LONG ☐ SHORT

QUICK ROLL CENTER POSITION
☒ LONG ☐ SHORT

SHIM
☐ 1.5 /mm

OFFSET
☒ STANDARD

REAR HUB
☐ M ☐ H ☐ ALU

FRONT

DOWNSTOP /mm **5**

REAR

FRONT

OUT ☐ **IN** ☒ .5

TOE /deg. **FINAL TOE IN** ☐ **3** **OUTBOARD TOE** ☐ **0**

SHIM UNDER SHOCK
☐ SHIM **1,5** /mm

SHIM FRONT
☐ SHIM **1,5** /mm

SHIM REAR
☐ SHIM **1,5** /mm

OUTER ACKERMANN POSITION
☐ 1 ☒ 2

INNER ACKERMANN POSITION
☐ 1 ☒ 2

SERVO SAVER

REAR

ANTI ROLL-BAR
☐ SHIM **0** /mm

SHIM UNDER SHOCK
☐ SHIM **0** /mm

SHIM FRONT/REAR
☐ 1.5 mm ☒ NO shim ☐ OTHER

INBOARD TOE
☒ SHIM **2,5** /mm ☐ 1,9 ☐ 1,5 ☐ 1,1 ☐ 0,75 ☐ 0

SHIM /mm ☒ 2,5 ☐ 1,9 ☐ 1,5 ☐ 1,1 ☐ 0,75 ☐ 0

SHIM /mm ☐ 2,5 ☐ 1,9 ☐ 1,5 ☐ 1,1 ☐ 0,75 ☐ 0

FRONT

FRONT ARM
☒ HARD (H) ☐ EXTRA-HARD (XH)

CAMBER /deg. **2**

REAR ARM
☒ HARD (H) ☐ EXTRA-HARD (XH)

CAMBER /deg. **1,5**

REAR

FRONT

DOWNSTOP /mm **5**

REAR

FRONT

BALANCE /g **15**

TOP DECK MULTI-FLEX SETTING
US TOP DECK

ECCENTER ☒ STANDARD ☐ 1

DIFF. POSITION
☒ UP ☐ DOWN

BALANCE /g

EU TOP DECK

REAR

BALANCE /g **10**

TOP DECK MULTI-FLEX SETTING
US TOP DECK

ECCENTER ☒ STANDARD ☐ 1

DIFF. POSITION
☒ UP ☐ DOWN

BALANCE /g

EU TOP DECK

FRONT

CHASSIS MULTI-FLEX SETTING
CHASSIS **5-cell**

CENTRAL ALU STAND

FRONT ALU STANDS (US)

REAR ALU STANDS (US)

BRACE (EU)

BRACE (EU)

REAR

CHASSIS MULTI-FLEX SETTING
CHASSIS **5-cell**

CENTRAL ALU STAND

FRONT ALU STANDS (US)

REAR ALU STANDS (US)

BRACE (EU)

BRACE (EU)