

SET-UP SHEET

RACE	ITCC		
TRACK	West Bridgeford		
NAME	Elliott Harper		
CITY / COUNTRY	Nottingham	UK	
CONTACT			
DATE	12/02/2008	TEMPERATURE / °F or °C	AIR
QUALIFYING POSITION	BEST LAP TIME / sec	FINAL POSITION	RACE LENGTH / minutes
	11.30		5
TRACK CONDITION	☐ CARPET ☐ ASPHALT ☐ TECHNICAL ☐ MIXED ☒ FAST		
TRACTION	☐ LOW ☒ MEDIUM ☐ HIGH		
FRONT		REAR	
TRANSMISSION			
FRONT PULLEY	38T	REAR PULLEY	
☐ LOOSE ☐ MEDIUM ☐ TIGHT		☐ LOOSE ☒ MEDIUM ☐ TIGHT	
ONE WAY DIFFERENTIAL		MIDDLE ONE WAY PULLEY	
☐ YES		☐ YES ☒ NO	
SOLID ONE WAY DIFF.		☐ YES ☒ NO	
SOLID AXLE		☒ YES ☐ NO	
PINION / T		SPUR GEAR / T	
FINAL DRIVE RATIO		ROLLOUT	
FRONT		REAR	
☐ ALU ☒ PLASTIC		☐ ALU ☒ PLASTIC	
SHOCKS			
XRAY SPRINGS			
#308393 Super Soft	☐ YELLOW	(D=1.4)	14 lb
#308384	☐ BLUE-GREEN	(D=1.5)	15 lb
#308394 Soft	☐ WHITE	(D=1.5)	17.5 lb
#308385	☐ LIGHT-BLUE	(D=1.6)	20 lb
#308395 Soft Medium	☐ BLUE	(D=1.6)	22.5 lb
#308386	☐ DARK-BLUE	(D=1.7)	25 lb
#308396 Medium	☐ VIOLET	(D=1.7)	28 lb
#308387	☐ LIGHT-PURPLE	(D=1.8)	30 lb
#308397 Medium Hard	☐ PURPLE	(D=1.8)	33 lb
#308388	☐ LIGHT-RED	(D=1.9)	35 lb
#308398 Hard	☐ RED	(D=1.9)	38 lb
#308373	☐ C 2.2		
#308374	☐ C 2.4		
#308375	☐ C 2.6	☒	
#308376	☒ C 2.8		
#308377	☐ C 3.0		
#308378	☐ C 3.2		
#308379	☐ C 3.4		
OTHER SPRING			
350	OIL / CST	350	
10mm shaft	LENGTH / mm	10mm shaft	
PRELOAD / mm			
3mm	REBOUND %	3mm	
☐ YES ☒ NO	FOAM INSERTS	☐ YES ☒ NO	
☐ YES ☒ NO	O-RING ON SHAFT	☐ YES ☒ NO	
☐ OPENED ☐ CLOSED		☐ HOLES IN PISTON	
1.4	THICKNESS / mm	1.2	THICKNESS / mm
ANTI-ROLL BAR			
Sorex 28	TIRES	Sorex 28	
DIAMETER / mm			
INSERTS			
ADDITIVE			
FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			
WHEELS			
S ☐ M ☐ H ☐	HARDNESS	S ☐ M ☐ H ☐	