

XRAY T2008

FRONT

CASTER 0° ☐ 2° ☐ 4° ☐ 6° ☒

DIVE ☐ **ROLL-CENTER** ☐

+0.75 ☒ 0.00 ☐ -0.75 ☐

SHIM /mm

+0.75 ☒ 0.00 ☐ -0.75 ☐

WHEELBASE/mm 0 1 1

4.5 **RIDE HEIGHT**/mm

SQUAT ROLL-CENTER

+0.75 ☒ 0.00 ☐ -0.75 ☐

+0.75 ☒ 0.00 ☐ -0.75 ☐

2 **RIDE HEIGHT**/mm

REAR

+0.75 ☒ 0.00 ☐ -0.75 ☐

+0.75 ☒ 0.00 ☐ -0.75 ☐

4.8 **RIDE HEIGHT**/mm

FRONT

C-HUB M ☐ H ☒ ALU ☐

STEERING BLOCK M ☐ H ☐ ALU ☒

OFFSET STANDARD ☒

SHIM 0 /mm

UPPER SHOCK POSITION 5 4 3 2 1

LONG ☐ **SHORT** ☒

QUICK ROLL CENTER POSITION 3 4 2 1

MEASURE UNDER ARM 8 7 6 5 4 3 2 1 0 -1 -2

DOWNSTOP /mm 0 1 2

REAR

SHIM 3 /mm

UPPER SHOCK POSITION 1 2 3 4 5 6

LONG ☐ **SHORT** ☒

QUICK ROLL CENTER POSITION 3 4 2 1

MEASURE UNDER ARM 8 7 6 5 4 3 2 1 0 -1 -2

DOWNSTOP /mm 0 1 2

FRONT

OUT 1 **IN** ☐

SHIM UNDER SHOCK SHIM 1 /mm

SHIM FRONT SHIM 2.3 /mm

SHIM REAR SHIM 2.3 /mm

OUTER ACKERMANN POSITION 1 2

INNER ACKERMANN POSITION 1 2

SERVO SAVER 1 2 3 4 5

REAR

FINAL TOE IN 2 **OUTBOARD TOE** 2.0

ANTI ROLL-BAR SHIM UNDER SHOCK SHIM /mm

SHIM FRONT/REAR 1.5 mm ☒

NO shim ☐

OTHER .75

INBOARD TOE SHIM /mm 2.25 = 3° 1.9 = 2.5° 1.5 = 2° 1.15 = 1.5° 0.75 = 1° 0.4 = 0.5° 0 = 0°

FRONT

1.5 **CAMBER** /deg.

FRONT ARM HARD (H) ☐ EXTRA-HARD (XH) ☒

REAR

3 **CAMBER** /deg.

REAR ARM HARD (H) ☐ EXTRA-HARD (XH) ☒

FRONT

BALANCE /g 10

ECCENTER STANDARD ☒ 1 ☐

DIFF. POSITION UP ☐ DOWN ☒

BALANCE /g 30

REAR

BALANCE /g 10

ECCENTER STANDARD ☒ 1 ☐

DIFF. POSITION UP ☒ DOWN ☐

BALANCE /g 30

FRONT

CHASSIS MULTI-FLEX SETTING

CHASSIS ☐

CENTRAL ALU STAND ☐

FRONT ALU STANDS (US) ☐

BRACE (EU) ☐

REAR

CHASSIS MULTI-FLEX SETTING

CHASSIS ☐

CENTRAL ALU STAND ☐

REAR ALU STANDS (US) ☐